
Product family datasheet

OSRAM DULUX S/E

Short CFLni, with 4-pin base for ECG operation



- Offices, public buildings Shops Supermarkets and department stores Hotels, restaurants

- Extremely economical Good quality of light Improved maintenance Low power consumption (7 W, 9 W, 11 W) Long service life Extremely low profile

Product family datasheet

Equipment / Accessories

- Suitable for operation on electronic control gear
-

Application advice

For more detailed application information and graphics please see product datasheet.

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

References / Links

For more information on QUICKTRONIC electronic control gear go to

- ▶ www.osram.com/QUICKTRONIC
-

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany