

## SHARXS HTI 1500 W/D7/60

SharXS HTI | Metal halide lamps, double-ended



### Areas of application

- Concert and effect lighting

### Product family features

- High efficiency thanks to short-arc technology
- High thermal load capacity thanks to eXtreme Seal (XS) technology - enables high pinch temperatures of up to 450 °C
- Hot restart capability
- Compact modular design - the same dimensions for all wattages within each SharXS family
- Pre-focus base for accurate lamp installation



## Product datasheet

### Technical data


#### Electrical data

Nominal wattage	1500.00 W
Nominal voltage	110 V
Ignition voltage	5.0 / 35 kVp
Nominal current	136 A
Lamp current	13.6 A

#### Photometrical data

Nominal luminous flux	145000 lm
Luminance	42000 cd/cm <sup>2</sup>
Color temperature	6000 K
Color rendering index Ra	>80

#### Dimensions & weight



Diameter	24.5 mm
Length	136.0 mm
Light center length (LCL)	57.5 mm

#### Temperatures & operating conditions

Maximum permitted pinch temperature	450 °C
-------------------------------------	--------

#### Lifespan

Lifespan	750 h
----------	-------

#### Additional product data

Base (standard designation)	SFc10-4
Product remark	May be operated from 1,200...1,500 W

## Product datasheet

### Capabilities

Burning position	Any
------------------	-----

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	05-03-2024
Primary Article Identifier	4008321285294   4008321349569
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321285294	OSRHTI1500D760	-	-	-
4008321285300	OSRHTI1500D760	-	-	-

## Product datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SharXS lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321285294	SHARXS HTI 1500 W/D7/60	Shipping carton box 1	182 mm x 87 mm x 58 mm	0.92 dm <sup>3</sup>	99.00 g
4008321285300	SHARXS HTI 1500 W/D7/60	Shipping carton box 10	312 mm x 186 mm x 194 mm	11.26 dm <sup>3</sup>	1140.00 g
4008321349569	SHARXS HTI 1500 W/D7/60	Shipping carton box 30	256 mm x 176 mm x 125 mm	5.63 dm <sup>3</sup>	1384.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

- Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.