

4ArXS HSD

Long-life short-arc metal halide lamps



Areas of application

- Entertainment
- Architainment

Product family benefits

- Especially long lifespan







Product family datasheet

Technical data

| | Electrical data | Photometri | cal data | Dimensions & weight | | | Additional product data |
|---------------------|--------------------|-----------------------------|---------------------------|---------------------|----------|------------------------------------|-----------------------------------|
| Product description | Nominal voltage | Nominal luminous flux | Color temper- ature | Diameter | Length | Light center length (LCL) | Base (standard designation) |
| 4ArXS HSD | 97.0 V | 12000 lm | 7000 K | 20.0 mm | 105.0 mm | | G12 |
| 4ArXS HSD 200 W/60 | 65.0 V | 13000 lm | 6000 K | 23.0 mm | 108.0 mm | 55.0 mm | GY9.5 |
| 4ArXS HSD 250 W/60 | 85.0 V | 17000 lm | 6000 K | 23.0 mm | 108.0 mm | 55.0 mm | GY9.5 |
| 4ArXS HSD 250 W/80 | 92.0 V | 17000 lm | 8000 K | 23.0 mm | 108.0 mm | 55.0 mm | GY9.5 |
| 4ArXS HSD 575 W/72 | 88.0 V | 45000 lm | 7200 K | 30.0 mm | 135.0 mm | 65.0 mm | GX9.5 |

Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

| Product description | Date of Declaration | Primary Article Identifier | Candidate List Substance 1 | Declaration No. in SCIP database | | | | | |
|---------------------|---------------------|---|------------------------------------|------------------------------------|--|--|--|--|--|
| 4ArXS HSD | 06-03-2024 | 4008321625847 | No declarable substances contained | No declarable substances contained | | | | | |
| 4ArXS HSD 200 W/60 | 05-03-2024 | 4050300424682 4008321114143 4008321625748 | | In work | | | | | |
| 4ArXS HSD 250 W/60 | 05-03-2024 | 4050300501925 4008321158161 4008321625762 | No declarable substances contained | In work | | | | | |
| 4ArXS HSD 250 W/80 | 05-03-2024 | 4008321625786 | No declarable substances contained | No declarable substances contained | | | | | |
| 4ArXS HSD 575 W/72 | 05-03-2024 | 4008321625809 | No declarable substances contained | No declarable substances contained | | | | | |

Product family datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, 4ArXS HSD lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

References / Links

Further information can be found in the following brochures, obtainable on request from OSRAM:

- "Technology and applications of metal halide lamps"
- "Guidelines for control gear and igniters for metal halide lamps"
- "Availability of control gear and igniters"
- "4ArXS has it all" Innovative metal halide lamps for creative architecture and effect lighting CD-ROM 4ArXS HSD

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.