

64386

Halogen lamps, current-controlled, single-ended



Areas of application

- Airfield lighting

Product family benefits

- Reduced operation and maintenance costs due to long lifetime
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

Product family features

- Dimmable
- Infrared radiation output that provides light in the worst of conditions



Product datasheet

Technical data

Product information

Order reference	64386 200W 6.6A
-----------------	-----------------


Electrical data

Lamp current	6.6 A
Nominal wattage	200.00 W

Photometrical data

Nominal luminous flux	4700 lm
Color rendering index Ra	100

Dimensions & weight



Diameter	13.5 mm
Length	47.0 mm
Light center length (LCL)	33.0 mm

Lifespan

Lifespan	1500 h
----------	--------

Additional product data

Base (standard designation)	G6.35
-----------------------------	-------

Capabilities

Burning position	s90
------------------	-----

Country specific categorizations

LIF	J1/39
-----	-------

Product datasheet

Order reference	64386 200W 6.6A
-----------------	-----------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	05-03-2024
Primary Article Identifier	4008321106407 4050300317755
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321106407	64386	Folding carton box 1	25 mm x 23 mm x 70 mm	0.04 dm ³	11.00 g
4008321106414	64386	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm ³	362.00 g
4050300317755	64386	Folding carton box 1	24 mm x 22 mm x 70 mm	0.04 dm ³	80.00 g
4050300317762	64386	Bundle 5	- x - x -		
4050300317779	64386	Shipping carton box 100	127 mm x 113 mm x 365 mm	5.24 dm ³	960.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on airfield lamps see the brochure:

"The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
