

## XBO R 100 W/45 C

XBO Xenon short-arc lamps with reflector 75...300 W | Xenon short-arc lamps with reflector 75...300 W



### Product family benefits

- Very high luminance (point light source)
- Continual color quality, irrespective of lamp type and lamp wattage
- Constant light color throughout the life of the lamp
- Long lamp life

### Product family features

- Color temperature: approx. 6,000 K (Daylight)
- High color rendering index:  $R_a >$
- High arc stability
- Hot restart capability
- Dimmable
- Instant light on starting
- Continuous spectrum in the visible range



# Product datasheet

## Technical data

### Electrical data


Nominal wattage	100.00 W
Lamp voltage	12...14 V <sup>1)</sup>
Lamp current	7.0...7.4 A
Type of current	DC
Lamp wattage	85 W
Rated wattage	100.00 W

<sup>1)</sup> Initial voltage range

### Light technical data

Focal length	45.0 mm
--------------	---------

### Dimensions & weight



Mounting length	77.0 mm
Cable length	125.0
Diameter	64.0 mm

### Lifespan

Lifespan	500 h
----------	-------

### Capabilities

Cooling	Forced
Burning position	p20
Application	Other

### Environmental information

## Product datasheet

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	05-03-2024
Primary Article Identifier	4050300367767
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	73407a33-6ed3-4b8a-9bb2-de48a2df4448

### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300367767	OSRXBOR10045COFR	-	-	-
4050300367767	OSRXBOR10045COFR	-	-	-

## Product datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure in both the hot and cold state, XBO lamps must only be operated in appropriate enclosed casings. Always use the protective jackets supplied when handling these lamps. They may only be used as open lamps if appropriate safety measures are taken. More information is available on request or can be found in the leaflet included with the lamp or the operating instructions.

The xenon lamp element is always under very high pressure. It may explode if subject to impact or damage. Therefore, spent XBO reflector lamps should be stored in an inaccessible place in the supplied casing or under the protection cap until they are sent for disposal.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300367767	XBO R 100 W/45 C	Folding carton box 1	- x - x -		
4050300367774	XBO R 100 W/45 C	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm <sup>3</sup>	291.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### References / Links

Further technical information on XBO lamps and information for manufacturers of operating equipment can be requested directly from OSRAM.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

---