

HBO 200 W/2 57 V

HBO Mercury short-arc lamps without reflector 50...200 W | Mercury short-arc lamps without reflector 50...200 W



Areas of application

- Fluorescence microscopy
- UV curing
- A variety of light guide applications

Product family benefits

- High radiance
- High radiant power in the UV and the visible range

Product family features

- Multi-line spectrum



Product datasheet

Technical data

Electrical data


Nominal voltage	57.0 V
Type of current	AC/DC
Rated wattage	200.00 W
Nominal wattage	200.00 W

Photometrical data

Nominal luminous flux	9500 lm
Luminous intensity	1000 cd ¹⁾

¹⁾ Typical initial photometric value

Dimensions & weight



Diameter	17.0 mm
Mounting length	102.0 mm ¹⁾
Length with base excl. base pins/connection	102.00 mm ¹⁾
Light center length (LCL)	40.0 mm ²⁾

¹⁾ Maximum

²⁾ Distance from end of base to tip of anode (cold)

Lifespan

Lifespan	400 / 200 h ¹⁾
----------	---------------------------

¹⁾ AC operation / DC operation

Additional product data

Base anode (standard designation)	SFc10-4
Base cathode (standard designation)	SFc10-4

Capabilities

Product datasheet

Burning position	s90 ¹⁾
Application	Other

¹⁾ Anode underneath

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	05-03-2024
Primary Article Identifier	4050300508153
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	0a543a28-ee8e-4f2f-be05-060615b8f13b

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300508153	OSRHBO2002L1	-	-	-
4050300508153	OSRHBO2002L1	-	-	-

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300508153	HBO 200 W/2 57 V	Folding carton box 1	82 mm x 42 mm x 191 mm	0.66 dm ³	238.00 g
4050300508160	HBO 200 W/2 57 V	Shipping carton box 10	306 mm x 235 mm x 200 mm	14.38 dm ³	2770.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Further technical information on HBO lamps and information for manufacturers of operating equipment can be requested directly from OSRAM.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
