

HPL 93729 750 W 240 V

HPL | High-performance lamps



Product family benefits

- Optimum use of the generated light in the spotlight



Product datasheet

Technical data

Product information

Order reference	93729 750W
-----------------	------------


Electrical data

Nominal voltage	240 V
Nominal wattage	750.00 W
On-mode power	810.00 W
Energy consumption in on-mode	810.0 kWh/1000h

Photometrical data

Color temperature	3200 K
Color rendering index Ra	100
Φuse value refers to luminous flux ..	360
Correlated color temperature CCT	3069 K
Useful luminous flux (Φuse)	16895 lm
Chromaticity coordinate x	0.432
Chromaticity coordinate y	0.403

Dimensions & weight



Diameter	19.0 mm
Length	104.0 mm
Length with base excl. base pins/connection	104.00 mm
Light center length (LCL)	60.3 mm
Illuminated field	7.5*11.5 mm ² ¹⁾
Filament diameter	11.5 mm

¹⁾ Type of filament 6-C8

Product datasheet

Lifespan

Lifespan	300 h
----------	-------

Additional product data

Base (standard designation)	2 pins
Lighting technology used	HL

Capabilities

Burning position	Any
------------------	-----

Certificates & standards

Energy efficiency class	G
-------------------------	---

Country specific categorizations

Order reference	93729 750W
ANSI code	Other

Logistical data

EAN 10 of contained light source	4052899246898
----------------------------------	---------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	22-05-2024
Primary Article Identifier	4050300654225 4052899246898
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300654225	HPL 93729 750 W 240 V	Folding carton box 1	- x - x -		
4050300654232	HPL 93729 750 W 240 V	Shipping carton box 12	174 mm x 150 mm x 145 mm	3.78 dm ³	953.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
