

ALLSEASON SUPER / ALLSEASON

Extra visibility under all weather conditions



Extra visibility

Due to yellow coating



Up to 30% more light

For better visibility and significantly shorter reaction times compared to standard halogen lamps



Better sight

Under all weather conditions



Better sight under all weather conditions

With up to 30% more light compared to standard lamps and an interference yellow coating ALLSEASON and ALLSEASON SUPER improve visibility while on the road under all weather conditions.

Product datasheet

Technical data

Product information

Product type (off-road vs. on-road)	Off-road \triangleq H4
Application (Category and Product specific)	Halogen headlight lamp

General Product Information

Global order reference	62204ALL
------------------------	----------

Electrical Data

Power input	100 / 80 W ¹⁾
Nominal voltage	12.0 V
Test voltage	13.2 V

¹⁾ Maximum

Photometric Data

Nominal luminous flux	2900/1700 lm
Luminous flux tolerance	± 15 / ± 15 %
Color temperature	3200 K

Physical Attributes & Dimensions

Diameter	17.0 mm
Product weight	25.90 g
Length	82.0 mm
Lamp base	P43t

Lifetime Data

Lifespan B3	45 / 100 hr
Lifespan Tc	90 / 200 hr

Capabilities

Technology	HAL
------------	-----

Certificates & standards

ECE category	
--------------	--

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	09-07-2024

Product datasheet

Primary article identifier	4052899369467 4052899369610 4052899369665 4062172358941
Candidate list substance 1	No declarable substances contained
Declaration no. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899369481	ALLSEASON SUPER / ALLSEASON \cong H4		- x - x -	19.40 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM