

# ALLSEASON SUPER / ALLSEASON H1

Extra visibility under all weather conditions



**Extra visibility**

Due to yellow coating



**Up to 30% more light**

For better visibility and significantly shorter reaction times compared to standard halogen lamps



**Better sight**

Under all weather conditions



**Better sight under all weather conditions**

With up to 30% more light compared to standard lamps and an interference yellow coating ALLSEASON and ALLSEASON SUPER improve visibility while on the road under all weather conditions.

# Product datasheet

## Technical data

### Product information

Order reference	64150ALS
Application (Category and Product specific)	Halogen headlight lamp

### Electrical data


Power input	68 W <sup>1)</sup>
Nominal voltage	12.0 V
Nominal wattage	55.00 W
Test voltage	13.2 V

<sup>1)</sup> Maximum

### Photometrical data

Luminous flux	1550 lm
Luminous flux tolerance	±15 %
Color temperature	3200 K

### Dimensions & weight



Diameter	9 mm
Product weight	8.00 g
Length	67.5 mm

### Lifespan

Lifespan B3	150 h
Lifespan Tc	350 h

### Additional product data

Base (standard designation)	P14.5s
-----------------------------	--------

## Product datasheet

### Capabilities

Technology	HAL
------------	-----

### Certificates & standards

ECE category	H1
--------------	----

### Country specific categorizations

Order reference	64150ALS
-----------------	----------

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	05-03-2024
Primary Article Identifier	4050300504544   4008321023629   4008321168733
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321168733	ALLSEASON SUPER / ALLSEASON H1	Hard Cover Box 2	- x - x -		110.00 g
4062172060523	ALLSEASON SUPER / ALLSEASON H1	Shipping carton box 10	268 mm x 126 mm x 125 mm	4.22 dm <sup>3</sup>	625.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



# OSRAM