

# SUPER H7

Up to 30% more light



**Up to 30% more light**

For better visibility and shorter reaction times compared to standard halogen lamps



**Enhanced illumination**

For extra confidence



**Convincing price-performance ratio**

For better visibility at a reasonable price



**Up to 30% more light on the road**

SUPER headlight lamps offer more performance for the most important lamp types. With up to 30% more light compared to standard lamps, signs, obstacles and hazards are more rapidly recognized.

# Product datasheet

## Technical data

### Product information

Order reference	64210SUP
Application (Category and Product specific)	Halogen headlight lamp

### Electrical data


Power input	58 W <sup>1)</sup>
Nominal voltage	12.0 V
Nominal wattage	55.00 W
Test voltage	13.2 V

<sup>1)</sup> Maximum

### Photometrical data

Luminous flux	1500 lm
Luminous flux tolerance	±10 %

### Dimensions & weight



Product weight	12.50 g
Length	59.0 mm

### Lifespan

Lifespan B3	340 h
Lifespan Tc	520 h

### Additional product data

Base (standard designation)	PX26d
-----------------------------	-------

### Capabilities

## Product datasheet

Technology	HAL
------------	-----

### Certificates & standards

ECE category	H7
--------------	----

### Country specific categorizations

Order reference	64210SUP
-----------------	----------

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4008321890375   4062172150156
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321890375	SUPER H7	Folding carton box 1	34 mm x 34 mm x 58 mm	0.07 dm <sup>3</sup>	16.00 g
4008321890382	SUPER H7	Bundle 10	170 mm x 69 mm x 58 mm	0.68 dm <sup>3</sup>	161.00 g
4008321890399	SUPER H7	Shipping carton box 100	356 mm x 186 mm x 129 mm	8.54 dm <sup>3</sup>	1762.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



# OSRAM