Product datasheet

OSRAM

ORIGINAL - PLASTIC MF BASE -

Original spare part





The cost-effective original spare parts

Discover our ORIGINAL signal lamps for printed circuit boards. These lamps with OSRAM's reliable OEM quality feature a wide product range and can be used for instrument and switch lighting.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	Auxiliary lamp
---	----------------

General Product Information

Global order reference	2721MF
Global order reference	

Electrical Data

Power input	1.2 W
Nominal voltage	12.0 V
Nominal wattage	1.20 W
Test voltage	13.5 V
Power input tolerance	±10 %

Photometric Data

Nominal luminous flux	6.4 lm
Luminous flux tolerance	±25 %

Physical Attributes & Dimensions

Diameter	5 mm
Product weight	1.18 g
Length	23.5 mm
Lamp base	B8.5d

Colors & materials

Base color	Jet black
------------	-----------

Lifetime Data

Lifespan B3	500 hr
Lifespan Tc	2000 hr

Capabilities

Thickness of PCB	1.6 mm
Technology	AUX

Certificates & standards

ECE category	-
Approval marks – approval	-

Product datasheet

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of declaration	09-07-2024	
Primary article identifier	4050300891255 4008321018342	
Candidate list substance 1	No declarable substances contained	
Declaration no. in SCIP database	In work	

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321096753	ORIGINAL - PLASTIC MF BASE 2721MF		- x - x -	0.94 dm³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.















