

XENARC ORIGINAL D3S

Four-year guarantee



The original spare parts with four-year guarantee

XENARC ORIGINAL lamps impress with a wide product range and the reliable OEM quality. Successfully used in millions of new vehicles from renowned manufacturers, whether as standard initial equipment or original spare parts. With up to 4,500 Kelvin color temperature, their light is closer to natural daylight than conventional halogen light with 3,200 Kelvin – and is thus more pleasant for the eyes. Thanks to the impressive intensity of the light, the lamps provide better visibility on the road. The durable lamps function as original spare parts of your motorcycle lamps and convince with their long lifetime. OSRAM provides a 4-year-guarantee for XENARC ORIGINAL lamps. Please note: XENARC lamp change is recommended to be carried out by a professional.

Product datasheet

Technical data


Electrical data

| | |
|-----------------------|---------|
| Power input | 35 W |
| Nominal voltage | 42.0 V |
| Nominal wattage | 35.00 W |
| Power input tolerance | ±3 % |
| Test voltage | 13.5 V |

Photometrical data

| | |
|-------------------------|---------|
| Luminous flux | 3200 lm |
| Color temperature | 4300 K |
| Luminous flux tolerance | ±15 % |

Dimensions & weight



| | |
|----------------|---------|
| Length | 83.2 mm |
| Diameter | 9 mm |
| Product weight | 60.20 g |

Lifespan

| | |
|-------------|---------|
| Lifespan B3 | 2000 h |
| Lifespan Tc | 4000 h |
| Guarantee | 4 years |

Additional product data

| | |
|-----------------------------|---------|
| Base (standard designation) | PK32d-5 |
|-----------------------------|---------|

Capabilities

| | |
|------------|-----|
| Technology | HID |
|------------|-----|

Product datasheet

Certificates & standards

| | |
|---------------------------|-------------------|
| ECE category | D3S ¹⁾ |
| Approval marks – approval | E1 approval |

¹⁾ To be operated only with approved electronic control gear

Environmental information


| Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh) | |
|--|---|
| Date of Declaration | 05-03-2024 |
| Primary Article Identifier | 4008321379627 4008321735201 4008321807649 4008321807663 4052899146365 4052899183650 4052899199569 4052899600485 4062172066754 4062172084574 4062172396837 |
| Candidate List Substance 1 | leadLead |
| CAS No. of substance 1 | 7439-92-1 |
| Safe Use Instruction | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration No. in SCIP database | 6ee45626-045c-415b-b12b-09cf7da79801 af212de5-b2c7-404c-acbe-c2ccabb83891 4ba45c38- 8f60-4555-8439-6505375ae44e f38b470a-745a- 439d-9286-890bc1f75779 8b6f0291-a6c0-4867- 8df0-c00e69eb2091 6e275300-8ea9-4bd5-bf1a- aa729070f942 b5de96fe-db0e-4cfb-9cd6- b43b44e32863 0a4d97a8-a9fd-4b6e-82eb- 08e719745496 49060069-850f-4c78-a673- 69f4a461d650 |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4052899199569 | XENARC ORIGINAL D3S | Folding carton box 1 | 53 mm x 46 mm x 93 mm | 0.23 dm ³ | 83.00 g |
| 4052899262386 | XENARC ORIGINAL D3S | Shipping carton box 4 | 115 mm x 101 mm x 103 mm | 1.20 dm ³ | 353.00 g |
| 4052899344495 | XENARC ORIGINAL D3S | Shipping carton box 48 | 371 mm x 256 mm x 232 mm | 22.03 dm ³ | 4533.00 g |
| 4052899600485 | XENARC ORIGINAL D3S | SCB 1 | 95 mm x 51 mm x 112 mm | 0.54 dm ³ | 84.00 g |
| 4052899600492 | XENARC ORIGINAL D3S | Shipping carton box 4 | 216 mm x 106 mm x 150 mm | 3.43 dm ³ | 410.00 g |
| 4062172030885 | XENARC ORIGINAL D3S | Shipping carton box 20 | 371 mm x 256 mm x 232 mm | 22.03 dm ³ | 2324.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File | |
|---|---|
|  | 360 Degree Image XENARC ORIGINAL D3S 66340 |

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM