

DLAEM CHROME PY21W

Only amber during operation




Chrome design

Thanks to cutting edge interference and absorber coating



Amber when ON

Only amber when operating, otherwise almost invisible



Homogenous appearance

Reflector has a fully homogenous chrome look



The design light with chrome look

OSRAM DIAEM CHROME signal lamps have a strikingly exclusive design: their chrome look made possible by a cutting edge interference and absorber coating. The lamps emit amber light only when operational. At other times, they are almost invisible and have no irritating color effects. DIAEM CHROME lamps are ideal for all indicator lights with clear covers.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	Auxiliary lamp
---	----------------

General Product Information

Global order reference	7507DC
------------------------	--------

Electrical Data

Power input	25 W
Nominal voltage	12.0 V
Nominal wattage	21 W
Power input tolerance	±6 %
Test voltage	13.5 V

Photometric Data

Nominal luminous flux	280 lm
Luminous flux tolerance	±20 %

Physical Attributes & Dimensions

Lamp base	BAU15s
Length	52.6 mm
Diameter	25.0 mm
Product weight	8.00 g

Lifetime Data

Lifespan B3	100 hr
Lifespan Tc	250 hr

Capabilities

Technology	AUX
------------	-----

Certificates & standards

ECE category	PY21W
--------------	-------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	09-07-2024

Product datasheet

Primary article identifier	4052899418011 4008321972774 4062172211529 4062172394857 4052899241657 4052899417977
Candidate list substance 1	No declarable substances contained
Declaration no. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321972781	DIADEM CHROME PY21W		- x - x -	4.68 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM