## Product datasheet

# **OSRAM**

# ORIGINAL - METAL BASE -

Original spare part





#### The cost-effective original spare parts for motorcycles

Discover OSRAM's ORIGINAL signal lamps with metal bases high-quality original spare parts for motorcycle lamps. Due to the wide product range, the lamps can be used for different applications. Use these lamps for example as position and parking lights or for number plate and side position lights of your motorcycle.

# Product datasheet

#### Technical data

#### **Product information**

Application (Category and Product specific)	Auxiliary lamp	
General Product Information		
Global order reference	3894	

#### **Electrical Data**

Power input	3 W
Nominal voltage	12.0 V
Nominal wattage	3 W
Power input tolerance	±10 %
Test voltage	13.5 V

#### **Photometric Data**

Nominal luminous flux	22 lm
Luminous flux tolerance	±20 %

### **Physical Attributes & Dimensions**

Lamp base	BA9s
Length	23.9 mm
Diameter	9 mm
Product weight	1.87 g

#### Lifetime Data

Lifespan B3	1000 hr
Lifespan Tc	2000 hr

#### Capabilities

Technology	AUX

\_

#### **Certificates & standards**

ECE category

## Environmental & Regulatory Information

## Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of declaration

01-07-2024

# Product datasheet

Primary article identifier	4008321095725
Declaration no. in SCIP database	In work

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321095749	ORIGINAL - METAL BASE 3894		- x - x -	0.94 dm³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.











