Product datasheet



LEDriving PX-5

LED daytime running light for retrofit





LED pixel technology Dynamic appearance thanks to faceted optic and dotted pixel technology



LED daytime running light compatible with a wide range of car models and easy to install



5200 K For drivers who want to increase visibility during the day



Stylish highlights for your car

LEDriving PX-5 serves as a high performance and energyefficient daytime running light for retrofitting on your vehicle. With its patterned diode design of five LEDs, the LEDriving PX-5 gives your vehicle a modern and stylish look. This daytime running light system is compatible with a wide range of vehicle models and is easy to install. The careful design of the LEDriving system ensures a horizontal tilt of 10 degrees. In addition, the left-hand and right-hand lamps can be switched, thus making installation uncomplicated. Furthermore, the high color temperature of 5,200 Kelvin and long life of up to 5,000 hours provide endless driving pleasure with LEDriving PX-5. OSRAM provides a 3-year guarantee for this product. Note: LEDriving PX-5 is certified according to ECE, SAE and CCC regulations (ECE E4 approval; ECE R87 approval).

Technical data

General Product Information

Global order reference	LEDDRL301
- •	

Electrical Data

Nominal voltage	12.0 V
Nominal wattage	12.50 W

Photometric Data

Color temperature	5200 К
Nominal luminous flux	550 lm

Physical Attributes & Dimensions

Length	160.0 mm
Product weight	552.00 g
Width	30.0 mm
Height	23.0 mm

Lifetime Data

Guarantee	3 years
Additional product data	
Connector to lamp	Wire Kit

Capabilities

Technology	LED
------------	-----

Certificates & standards

Approval marks – approval	E4 approval
Standards	ECE R87

Logistical data

Commodity code

85122000900

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of declaration

26-06-2024

Product datasheet

Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	7a05b6d4-2aed-41c9-afdf-7da8dfd39471

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899089563	LEDriving PX-5		- x - x -	31.28 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
1	User instruction LED Daytime Running Light Kit LEDDRL301 (User Manual)

Legal advice

ECE E4 approvalECE R87 approval

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

















