

## LEDCOMFO DL ACE | LED downlights



# Product datasheet

## Technical data

### Product information

Order reference	LEDCOMFO DL ACE
-----------------	-----------------

### Electrical data

Operating mode	ECG
Nominal wattage	5.5 W
Connected load	5.5 W
Nominal voltage	220...240 V
Supply voltage	220...240 V
Mains frequency	50/60 Hz

### Photometrical data

Color temperature	4000 K
Color temperature [AGMP]	4000 K
Luminous flux	303 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

### Light technical data

Beam angle	90 °
------------	------

### Dimensions & weight

Length	0.0 mm
Diameter	96.0 mm
Height	60.0 mm
Product weight	0.1 kg

### Colors & materials

Body material	aluminium
Product color	white
Cover material	PC

### Temperatures & operating conditions

Ambient temperature range	-20...+35 °C
---------------------------	--------------

### Additional product data

Type of cover	diffuser
---------------	----------

## Product datasheet

### Capabilities

Type of installation	recessed
Type of connection	with single terminals

### Certificates & standards

Protection class	insulation class II (safety insulation)
Type of protection	IP20

### Country specific categorizations

Order reference	LED COMFO DL ACE
-----------------	------------------

## Product datasheet

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899225121		Folding carton box 1	- x - x -		
4052899225138		Shipping carton box 40	540 mm x 432 mm x 228 mm	53.19 dm <sup>3</sup>	6307.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.