

LEDCOMFO DL ACE

LED downlights







Product family datasheet

Technical data

	Product informatio n	Electrical data			
Product description	Order	Operating mode	Connected load	Nominal	Nominal
· · · · · · · · · · · · · · · · · · ·		- p - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1			
· ·	reference	- F		wattage	voltage
-	reference LEDCOMFO	ECG	5.5 W		

			Photometrical data			
Product description	Supply voltage	Mains frequency	Color temperature [AGMP]	Color temper- ature	Luminous flux	Color render- ing index Ra
-	220240 V	50/60 Hz	4000 K	4000 K	303 lm	>80

		Light technical data	Dimensions & weight		Colors & materials	
Product description	Color rendering index Ra [AGMP]	Beam angle	Length	Diameter	Height	Body material
-	>80	90 °	0.0 mm	96.0 mm	60.0 mm	aluminium

			Temperatures & operating conditions	Capabilities
Product description	Product color	Cover material	Ambient temperature range	Type of installation
-	white	PC	-20+35 °C	recessed

		Certificates & standards	
Product description	Type of connection	Protection class	Type of protection
_	with single terminals	insulation class II (safety insulation)	IP20

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.