

LEDCOMFO SPOT LIGHT 6 W

Indoor LED spotlights



Areas of application

- Cozy spot lighting for home
- Replacement for luminaires that use MR11, MR16 lamps and conventional spots
- Corridors
- Study rooms
- Glass cabinets
- Living rooms
- Bedrooms
- Nighttime lighting and star lighting effect

Product family benefits

- Suitable for use in areas with low ceilings thanks to compact design
- Various options to highlight target areas
- No extra maintenance thanks to long lifetime of LED
- Long lifetime of LED
- Strong light distribution due to special designed Fresnel lens
- Effective glare control due to adjustable head, concave stepping and Fresnel lens
- Energy savings of up to 80 % compared to luminaires that use halogen lamps
- Easy installation thanks to subtle locking system

Product family features

- Luminaire with energy-saving LED spot
- Lifetime (L70): up to 20,000 h
- Partially adjustable head
- Beam angle: 14°, 24°, 36°



non EU



Product family datasheet

Technical data

| Product description | Product information | Electrical data | | | |
|------------------------|---------------------|-----------------|----------------|----------------|-----------------|
| | Order reference | Nominal wattage | Connected load | Supply voltage | Nominal voltage |
| LEDCOMFO SL 6 W 2700 K | LEDCOMFO SL 6W | 6 W | 6 W | 220...240 V | 220...240 V |

| Product description | Mains frequency | Photometrical data | | | | |
|------------------------|-----------------|--------------------------|-------------------|---------------|--------------------------|---------------------------------|
| | | Color temperature [AGMP] | Color temperature | Luminous flux | Color rendering index Ra | Color rendering index Ra [AGMP] |
| LEDCOMFO SL 6 W 2700 K | 50 Hz | 2700 K | 2700 K | 330 lm | >80 | >80 |

| Product description | Light technical data | Dimensions & weight | | | | Colors & materials |
|------------------------|---------------------------|---------------------|---------|----------|---------|--------------------|
| | Beam angle | Length | Width | Diameter | Height | Body material |
| LEDCOMFO SL 6 W 2700 K | medium distribution, 36 ° | 0.0 mm | 74.0 mm | 90.0 mm | 70.0 mm | aluminium |

| Product description | Product color | Cover material | Temperatures & operating conditions | Certificates & standards | |
|------------------------|---------------|----------------|-------------------------------------|---|--------------------|
| | | | Ambient temperature range | Protection class | Type of protection |
| LEDCOMFO SL 6 W 2700 K | white | PC | -20...+40 °C | insulation class II (safety insulation) | IP20 |

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.