

OPTV DL 9 W 865

OPTIVALU Down Light 4 | LED downlights



Areas of application

- Replacement for downlight applications with compact fluorescent lamps
- Offices
- Retail
- Shopping malls
- Lobbies
- Corridors
- Commercial buildings

Product family benefits

- Wide beam angle
- High light uniformity and glare-free light thanks to diffuser
- Variable installation possibilities
- Energy savings of up to 60 % compared to luminaires that use CFL
- Short pay-off time

Product family features

- Housing made of 1.2 mm thick metal
- High luminous efficacy: up to 100 lm/W
- Lifetime: up to 50,000 h
- Wide range of different versions





Product datasheet

Technical data

Product information

Electrical data

Operating mode	ECG
Nominal wattage	9 W
Connected load	9 W
Nominal voltage	220240 V
Supply voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	6500 K
Color temperature [AGMP]	6500 K
Luminous flux	850 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

Light technical data

Beam angle 90	90 °
---------------	------

Dimensions & weight

Length	117.0 mm	
Height	88.0 mm	
Product weight	0.2 kg	

Colors & materials

Body material	aluminium	
Product color	white	
Cover material	PC	

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Additional product data

Product datasheet

Capabilities

Type of installation	recessed	
Type of connection	with single terminals	

Certificates & standards

Protection class	insulation class I (protective earthing)	
Type of protection	IP20	

Country specific categorizations

Order reference	OPTV DL 409 865

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899263826	OPTV DL 9 W 865	Folding carton box 1	- x - x -		
4052899263833	OPTV DL 9 W 865	Shipping carton box	310 mm x 164 mm x 248 mm	12.61 dm³	1471.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.