

# **OPTV DL 21 W 865**

## OPTIVALU Down Light 8 | LED downlights



#### Areas of application

- Replacement for downlight applications with compact fluorescent lamps
- Offices
- Retail
- Shopping malls
- Lobbies
- Corridors
- Commercial buildings

### Product family benefits

- Energy savings of up to 60 % compared to luminaires that use CFL
- Wide beam angle
- High light uniformity and glare-free light thanks to diffuser
- Variable installation possibilities
- Short pay-off time

### Product family features

- Wide range of different versions
- Lifetime: up to 50,000 h
- High luminous efficacy: up to 100 lm/W  $\,$
- Housing made of 1.2 mm thick metal





## Product datasheet

#### Technical data

### **Product information**

#### **Electrical data**

Operating mode	ECG
Nominal wattage	21 W
Connected load	21 W
Nominal voltage	220240 V
Supply voltage	220240 V
Mains frequency	50/60 Hz

### Photometrical data

Color temperature	6500 K
Color temperature [AGMP]	6500 K
Luminous flux	2100 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

## Light technical data

## **Dimensions & weight**

Length	217.0 mm
Height	110.0 mm
Product weight	0.3 kg

### Colors & materials

Body material	aluminium
Product color	white
Cover material	PC

## Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

## Additional product data

Type of cover diffuser
------------------------

# Product datasheet

# Capabilities

Type of installation	recessed	
Type of connection	with single terminals	

## Certificates & standards

Protection class	insulation class I (protective earthing)	
Type of protection	IP20	

# **Country specific categorizations**

Order reference	OPTV DL 821 865

### Product datasheet

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899263888	OPTV DL 21 W 865	Folding carton box 1	- x - x -		
4052899263895	OPTV DL 21 W 865	Shipping carton box 4	510 mm x 264 mm x 296 mm	39.85 dm³	2783.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.