

## OPTV DL 30 W 840 DIM

OPTIVALU Down Light 8 | Dimmable



### Areas of application

- Replacement for downlight applications with compact fluorescent lamps
- Offices
- Retail
- Shopping malls
- Lobbies
- Corridors
- Commercial buildings

### Product family benefits

- Energy savings of up to 60 % compared to luminaires that use CFL
- Wide beam angle
- High light uniformity and glare-free light thanks to diffuser
- Variable installation possibilities
- Short pay-off time

### Product family features

- Housing made of 1.2 mm thick metal
- High luminous efficacy: up to 100 lm/W
- Lifetime: up to 50,000 h
- Wide range of different versions



# Product datasheet

## Technical data

### Product information

Order reference	OPTV DL 830 840
-----------------	-----------------

### Electrical data

Operating mode	ECG
Nominal wattage	30 W
Connected load	30 W
Nominal voltage	220...240 V
Supply voltage	220...240 V
Mains frequency	50/60 Hz

### Photometrical data

Color temperature	4000 K
Color temperature [AGMP]	4000 K
Luminous flux	3000 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

### Light technical data

Beam angle	90 °
------------	------

### Dimensions & weight

Length	0.0 mm
Diameter	217.0 mm
Height	110.0 mm
Product weight	0.4 kg

### Colors & materials

Body material	aluminium
Product color	white
Cover material	PC

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

### Additional product data

Type of cover	diffuser
---------------	----------

## Product datasheet

### Capabilities

Type of installation	recessed
Type of connection	with single terminals

### Certificates & standards

Protection class	insulation class II (safety insulation)
Type of protection	IP20
Protection against ignition and fire	F

### Country specific categorizations

Order reference	OPTV DL 830 840
-----------------	-----------------

## Product datasheet

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899322721	OPTV DL 30 W 840 DIM	Folding carton box 1	- x - x -		
4052899322738	OPTV DL 30 W 840 DIM	Shipping carton box 4	510 mm x 264 mm x 296 mm	39.85 dm <sup>3</sup>	3063.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.