

LEDTOUCH Louver UG 30 W 840

LEDTOUCH Louver UG | Indoor LED ceiling luminaires



Areas of application

- Offices, schools
- Museums
- Hospitals

Product family benefits

- Easy and quick installation
- Elegant homogenous design
- Good glare reduction (UGR < 19)
- High-performance LEDs

Product family features

- Lifetime: up to 50,000 h
- High system efficiency: up to 100 lm/W





Product datasheet

Technical data

Product information

Electrical data

Operating mode	ECG
Nominal wattage	30 W
Connected load	30 W
Nominal voltage	220240 V
Supply voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 К
Color temperature [AGMP]	4000 K
Luminous flux	3150 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

Light technical data

Dimensions & weight

Length	597.0 mm
Width	597.0 mm
Height	110.0 mm
Product weight	4.9 kg

Colors & materials

Body material	steel		
Product color	signal white (RAL 9003)		
Cover material	PC		

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Additional product data

Type of cover	diffuser

Product datasheet

Capabilities

Type of installation	recessed
----------------------	----------

Certificates & standards

Protection class	insulation class I (protective earthing)	
Type of protection	IP20	

Country specific categorizations

Order reference	LDTH LOU LL0401

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899431263	LEDTOUCH Louver UG 30 W 840	Folding carton box 1	- x - x -		
4052899431270	LEDTOUCH Louver UG 30 W 840	Shipping carton box 2	640 mm x 290 mm x 665 mm	123.42 dm ³	11196.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.