

## LEDTOUCH DOWNLIGHT 3

Indoor LED spotlights with 3 inch diameter



### Areas of application

- Offices
- Shopping malls
- Retail
- Airports
- Hospitals
- Metro stations
- Public buildings
- For indoor use only

### Product family benefits

- Good glare reduction (UGR < 19)
- Even light distribution thanks to Fresnel and micro lenses
- Clear cast shadows (no ghost shadows) due to Chip-On-Board technology

### Product family features

- Available with different wattages, beam angles and in various sizes
- Lifetime: up to 50,000 h



## Product family datasheet

### Technical data

Product description	Product information	Electrical data			
	Order reference	Operating mode	Connected load	Nominal wattage	Nominal voltage
LDTH DL 3 11 W 827 38°	LDTH DL 311 L38	ECG	11 W	11 W	220...240 V
LDTH DL 3 11 W 830 26°	LDTH DL 311 L26	ECG	11 W	11 W	220...240 V
LDTH DL 3 11 W 840 26°	LDTH DL 311 L26	ECG	11 W	11 W	220...240 V
LDTH DL 3 11 W 830 38°	LDTH DL 311 L38	ECG	11 W	11 W	220...240 V
LDTH DL 3 11 W 840 38°	LDTH DL 311 L38	ECG	11 W	11 W	220...240 V

Product description	Supply voltage	Mains frequency	Photometrical data			
			Color temperature	Color temperature [AGMP]	Luminous flux	Color rendering index Ra
LDTH DL 3 11 W 827 38°	220...240 V	50/60 Hz	2700 K	2700 K	950 lm	>80
LDTH DL 3 11 W 830 26°	220...240 V	50/60 Hz	3000 K	3000 K	950 lm	>80
LDTH DL 3 11 W 840 26°	220...240 V	50/60 Hz	4000 K	4000 K	1000 lm	>80
LDTH DL 3 11 W 830 38°	220...240 V	50/60 Hz	3000 K	3000 K	950 lm	>80
LDTH DL 3 11 W 840 38°	220...240 V	50/60 Hz	4000 K	4000 K	1000 lm	>80

Product description	Color rendering index Ra [AGMP]	Light technical data	Dimensions & weight			Colors & materials
		Beam angle	Length	Diameter	Height	Body material
LDTH DL 3 11 W 827 38°	>80	38 °	0.0 mm	85.0 mm	110.0 mm	diecast aluminium
LDTH DL 3 11 W 830 26°	>80	26 °	0.0 mm	85.0 mm	110.0 mm	diecast aluminium
LDTH DL 3 11 W 840 26°	>80	26 °	0.0 mm	85.0 mm	110.0 mm	diecast aluminium
LDTH DL 3 11 W 830 38°	>80	38 °	0.0 mm	85.0 mm	110.0 mm	diecast aluminium
LDTH DL 3 11 W 840 38°	>80	38 °	0.0 mm	85.0 mm	110.0 mm	diecast aluminium

## Product family datasheet

Product description	Product color	Cover material	Temperatures & operating conditions	Capabilities
			Ambient temperature range	Type of installation
LDTH DL 3 11 W 827 38°	light grey (RAL 7035)	glass	-15...+40 °C	recessed
LDTH DL 3 11 W 830 26°	light grey (RAL 7035)	glass	-15...+40 °C	recessed
LDTH DL 3 11 W 840 26°	light grey (RAL 7035)	glass	-15...+40 °C	recessed
LDTH DL 3 11 W 830 38°	light grey (RAL 7035)	glass	-15...+40 °C	recessed
LDTH DL 3 11 W 840 38°	light grey (RAL 7035)	glass	-15...+40 °C	recessed

Product description	Type of connection	Certificates & standards	
		Protection class	Type of protection
LDTH DL 3 11 W 827 38°	cable with plug	insulation class II (safety insulation)	IP20
LDTH DL 3 11 W 830 26°	cable with plug	insulation class II (safety insulation)	IP20
LDTH DL 3 11 W 840 26°	cable with plug	insulation class II (safety insulation)	IP20
LDTH DL 3 11 W 830 38°	cable with plug	insulation class II (safety insulation)	IP20
LDTH DL 3 11 W 840 38°	cable with plug	insulation class II (safety insulation)	IP20

## Product family datasheet

---

### Equipment / Accessories

- Safety cable for reflector included (hole for fixing the cable existing)
- 

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.