

LDTH DL 6 40 W 827 28°

LEDTOUCH DOWNLIGHT 6 | Indoor LED spotlights with 6 inch diameter



Areas of application

- Offices
- Shopping malls
- Retail
- Airports
- Hospitals
- Metro stations
- Public areas
- For indoor use only

Product family benefits

- Good glare reduction (UGR < 19)
- Even light distribution thanks to Fresnel and micro lenses
- Clear cast shadows (no ghost shadows) due to Chip-On-Board technology

Product family features

- Available with different wattages, beam angles and in various sizes
- Lifetime: up to 50,000 h



Product datasheet

Technical data

Product information

Order reference	LDTH DL 640 L28
-----------------	-----------------

Electrical data

Operating mode	ECG
Nominal wattage	40 W
Connected load	40 W
Nominal voltage	220...240 V
Supply voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	2700 K
Color temperature [AGMP]	2700 K
Luminous flux	3800 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

Light technical data

Beam angle	28 °
------------	------

Dimensions & weight

Length	0.0 mm
Diameter	160.0 mm
Height	160.0 mm
Product weight	1.5 kg

Colors & materials

Body material	diecast aluminium
Product color	light grey (RAL 7035)
Cover material	glass

Temperatures & operating conditions

Ambient temperature range	-15...+40 °C
---------------------------	--------------

Additional product data

Type of cover	cover
---------------	-------

Product datasheet

Capabilities

Type of installation	recessed
Type of connection	cable with plug

Certificates & standards

Protection class	insulation class II (safety insulation)
Type of protection	IP20

Country specific categorizations

Order reference	LDTH DL 640 L28
-----------------	-----------------

Product datasheet

Equipment / Accessories

- Safety cable for reflector included (hole for fixing the cable existing)
-

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899423510	LDTH DL 6 40 W 827 28°	Folding carton box 1	- x - x -		
4052899423527	LDTH DL 6 40 W 827 28°	Shipping carton box 6	571 mm x 386 mm x 212 mm	46.73 dm ³	11454.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
