

LDTH DL 8 40 W 840 55°

LEDTOUCH DOWNLIGHT 8 | Indoor LED spotlights with 8 inch diameter



Areas of application

- Offices
- Shopping malls
- Retail
- Airports
- Metro stations
- Public areas
- For indoor use only

Product family benefits

- Good glare reduction (UGR < 19)
- Even light distribution thanks to Fresnel and micro lenses
- Clear cast shadows (no ghost shadows) due to Chip-On-Board technology

Product family features

- Available with different wattages, beam angles and in various sizes
- Lifetime: up to 50,000 h





Product datasheet

Technical data

Product information

Order reference	LDTH DL 840 L55
-----------------	-----------------

Electrical data

Operating mode	ECG
Nominal wattage	40 W
Connected load	40 W
Nominal voltage	220240 V
Supply voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 K	
Color temperature [AGMP]	4000 K	
Luminous flux	4000 lm	
Color rendering index Ra	>80	
Color rendering index Ra [AGMP]	>80	

Light technical data

Dimensions & weight

Length	0.0 mm
Diameter	210.0 mm
Height	200.0 mm
Product weight	2 kg

Colors & materials

Body material diecast aluminium		
Product color	light grey (RAL 7035)	
Cover material	glass	

Temperatures & operating conditions

Ambient temperature range	-15+40 °C
---------------------------	-----------

Additional product data

Product datasheet

Capabilities

Type of installation	recessed	
Type of connection	cable with plug	

Certificates & standards

Protection class	insulation class II (safety insulation)	
Type of protection	IP20	

Country specific categorizations

Order reference	LDTH DL 840 L55

Product datasheet

Equipment / Accessories

- Safety cable for reflector included (hole for fixing the cable existing)

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899422759	LDTH DL 8 40 W 840 55°	Folding carton box 1	- x - x -		
4052899422766	LDTH DL 8 40 W 840 55°	Shipping carton box 4	486 mm x 486 mm x 257 mm	60.70 dm ³	10146.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.