OSRAM

XENARC ULTRA LIFE D4S

Superior life and 10 year guarantee





10 year OSRAM guarantee

For a worry-free driving pleasure. Refer to www.osram.com/am-guarantee for precise conditions



Extra lifetime Up to four times longer lifetime compared to standard xenon lamps



More durability For longer replacement cycles and additional reliability and comfort



The durable light with up to four times longer lifetime

XENARC ULTRA LIFE xenon lamps were developed with durability in mind. These long-life headlight lamps make life just that little bit more hassle-free, thanks to a lifetime up to four times longer compared to standard xenon lamps. Besides, these reliable lights impress with a service life up to 300,000 km (with an average annual mileage of 14,259 km and 60% light on)! For XENARC ULTRA LIFE lamps, OSRAM provides a unique 10 year guarantee for end consumers (www.osram.com/am-guarantee). Thus, you not only save money on costly replacements, but also save yourself future stress and downtime. Please note: XENARC lamp change is recommended to be carried out by a professional.

Technical data

Electrical Data

Power input	35 W
Nominal voltage	42.0 V
Nominal wattage	35 W
Test voltage	13.5 V
Power input tolerance	±3 %

Photometric Data

Nominal luminous flux	3200 lm
Luminous flux tolerance	±15 %

Physical Attributes & Dimensions

Diameter	9 mm
Product weight	16.30 g
Length	77.3 mm
Lamp base	P32d-5

Lifetime Data

Guarantee	10 years

Capabilities

Technology	HID
------------	-----

Certificates & standards

ECE category	D4S ¹⁾
Approval marks – approval	E1 approval

1) To be operated only with approved electronic control gear

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of declaration 09-07-2024		
Primary article identifier	4052899425637 4052899429772	
Candidate list substance 1	No declarable substances contained	
Declaration no. in SCIP database	In work	



ref_pim_amsp_productinfographic s

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899425644	XENARC ULTRA LIFE D4S		- x - x -	1.20 dm³	
4052899429789	XENARC ULTRA LIFE D4S		- x - x -	4.01 dm ³	
4062172022095	XENARC ULTRA LIFE D4S		- x - x -	1.56 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
≍	Brochures ULTRA LIFE Leaflet EN
Ľ	ref_pim_amsp_product360degreeimages XENARC ULTRA LIFE D4S 66440ULT

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.





R







