Product family datasheet



LEDriving BASIC P21W



Product family datasheet

Technical data

	Product information			General Product Information	Electrical Data	
Product description		n (Category ct specific)	Product type (off- road vs. on-road)	Global order reference	Power input	Nominal voltage
LEDriving BASIC ≜ P21W	Mainly used for signal/ indicator applications		Off-road ≙ P21W	7356CW	1.44 W	12.0 V
				Photometric Data		Physical Attributes & Dimensions
Product description	Nominal w	vattage	Test voltage	Nominal luminous flux	Luminous flux tolerance	Diameter
LEDriving BASIC \doteq P21W	1 W		13.5 V	85 lm	±20 %	20.0 mm
	Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Lifespan B3	Lifespan Tc	Technology	Primary article identifier	Candidate substance	
LEDriving BASIC \triangleq P21W	2000 hr	2000 hr	LED	4052899463318 4052899414471	Lead	

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC ≜ P21W	7439-92-1	The identification of	d093b426-00c5-
		the Candidate List	4f97-9516-
		substance is	27dd98167ef2 ccdfe4
		sufficient to allow	4b-95fd-4b60-97d3-
		safe use of the	317a31be77c4 c5836
		article.	93a-46e5-4c4f-83a9-
			dac2ada6ba15

Product family datasheet

Download Data

	File
*	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

