OSRAM

LEDriving BASIC P21/5W



Product family datasheet

Technical data

	Product information			General Product Information	Electrical Data	
Product description	Product type (off- road vs. on-road)		tion (Category oduct specific)	Global order reference	Power input	Nominal voltage
LEDriving BASIC ≜ P21/5W	Off-road ≙ P21/5W	•	used for indicator tions	1357CW	1.44 W	12.0 V
				Photometric Data		Physical Attributes & Dimensions
Product description	Nominal watt	age	Test voltage	Nominal luminous flux	Luminous flux tolerance	Diameter
LEDriving BASIC	1 W		13.5 V	85/25 lm	±20 %	20.0 mm
	Lifetime Data Capa		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Lifespan Li	ifespan	Technology	Date of declaration	Primary art	!-I-

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC	Lead	7439-92-1	The identification of	9bf3b981-7442-
			the Candidate List	439c-a86d-
			substance is	e513fc794734 fe6d7
			sufficient to allow	1fd-c80e-400d-8cc2-
			safe use of the	14ed29394294 1d48
			article.	0114-7d33-4144-
				80cc-0d5f7210d25e

В3

2000 hr

Tc

2000 hr

LED

09-07-2024

identifier

4052899463295 | 4052899414518 | 4052899414495

Product family datasheet

Download Data

File



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

