

# LEDiving BASIC T4W



## Product family datasheet

### Technical data

| Product description               | Product information                                      |                                     | General Product Information | Electrical Data |                 |
|-----------------------------------|--|-------------------------------------|-----------------------------|-----------------|-----------------|
|                                   | Application (Category and Product specific)              | Product type (off-road vs. on-road) | Global order reference      | Power input     | Nominal voltage |
| LEDDriving BASIC $\triangleq$ T4W | Mainly used for signal/ indicator/ interior applications | Off-road $\triangleq$ T4W           | 3750CW                      | 0.78 W          | 12.0 V          |

| Product description               | Nominal wattage | Test voltage | Photometric Data      |                         | Physical Attributes & Dimensions |
|-----------------------------------|-----------------|--------------|-----------------------|-------------------------|----------------------------------|
|                                   |                 |              | Nominal luminous flux | Luminous flux tolerance | Diameter                         |
| LEDDriving BASIC $\triangleq$ T4W | 0 W             | 13.5 V       | 30 lm                 | $\pm 20$ %              | 9.5 mm                           |

| Product description               | Lifetime Data |             | Capabilities | Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                            |
|-----------------------------------|---------------|-------------|--------------|---|----------------------------|
|                                   | Lifespan B3   | Lifespan Tc | Technology   | Primary article identifier  | Candidate list substance 1 |
| LEDDriving BASIC $\triangleq$ T4W | 2000 hr       | 2000 hr     | LED          | 4052899463271  <br>4052899414617  <br>4052899463066  <br>4052899414655  | Lead                       |

| Product description               | CAS No. of substance 1 | Safe use instruction   | Declaration no. in SCIP database  |
|-----------------------------------|------------------------|--|---|
| LEDDriving BASIC $\triangleq$ T4W | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 9add2d47-cd43-47d0-90e8-b42553d559f6 aadf4566-2f5c-420c-940e-ab52c14c2128 dc70588f-5433-4c78-9a81-18450deb8f7c 4ed996ff-d5b8-4576-b168-a975922e67e5 |

## Product family datasheet

---

### Download Data

| File  |   |
|---|---|
|  | Brochures<br>LEDriving Retrofits - Exchange overview (EN) |

#### Legal advice

Not ECE conform Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

#### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.