

LEDiving BASIC R5W



Product family datasheet

Technical data

Product description	Product information			Electrical data		
	Order reference	Product type (off-road vs. on-road)	Application (Category and Product specific)	Power input	Nominal voltage	Nominal wattage
LEDDriving BASIC \cong R5W	5107CW	Off-road \cong R5W	Mainly used for signal/ indicator applications	0.96 W	12.0 V	0.80 W

Product description	Test voltage	Photometrical data		Dimensions & weight	Lifespan		Capabilities
		Luminous flux	Luminous flux tolerance	Diameter	Lifespan B3	Lifespan Tc	Technology
LEDDriving BASIC \cong R5W	13.5 V	55 lm	± 20 %	19.0 mm	2000 h	2000 h	LED

Product description	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1
LEDDriving BASIC \cong R5W	21-06-2024	4052899414532 4052899414556 4052899427396 4052899463127 4052899463332	Lead	7439-92-1

Product description	Safe Use Instruction	Declaration No. in SCIP database
LEDDriving BASIC \cong R5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	4deab8c0-c089-4d6a-90f4-3738f5af799e a74edd59-fe84-466f-9e9c-d76036657cbc bfa7eecb-33b8-4a4a-bd2e-265775e7c10f 12c61241-8e84-49d2-aad6-61ee9185fc4c e8c7bd92-d6cb-4cf2-9e8f-8360bae74918

Product family datasheet

Download Data

File	
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.