

ECOFITZ LED WP 600 20W C857

ECOFITZ Water-proof | Damp-proof luminaires



Product datasheet

Technical data

Product information

Order reference	ECOFITZ LED WP
-----------------	----------------

Electrical data

Operating mode	ECG
Nominal wattage	20 W
Connected load	20 W
Nominal voltage	220...240 V
Supply voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	5700 K
Color temperature [AGMP]	5700 K
Luminous flux	2100 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

Light technical data

Beam angle	108 x 103 °
Light distribution	symmetric

Dimensions & weight

Length	590.0 mm
Width	83.0 mm
Height	64.0 mm
Product weight	0.6 kg

Colors & materials

Body material	PC
Product color	grey
Cover material	PC

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Product datasheet

Type of cover	cover
---------------	-------

Capabilities

Type of installation	surface-mounted/suspended mounting
----------------------	------------------------------------

Certificates & standards

Protection class	insulation class I (protective earthing)
Type of protection	IP65

Country specific categorizations

Order reference	ECOFITZ LED WP
-----------------	----------------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899467323	ECOFITZ LED WP 600 20W C857	Folding carton box 1	644 mm x 87 mm x 68 mm	3.81 dm ³	717.00 g
4052899467330	ECOFITZ LED WP 600 20W C857	Shipping carton box 12	662 mm x 276 mm x 282 mm	51.52 dm ³	9504.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.