

ECOFITZ LED WP 1200 40 W C857

ECOFITZ Water-proof | Damp-proof luminaires







Product datasheet

Technical data

Product information

Electrical data

Operating mode	ECG
Nominal wattage	40 W
Connected load	40 W
Nominal voltage	220240 V
Supply voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	5700 K
Color temperature [AGMP]	5700 K
Luminous flux	4400 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

Light technical data

Beam angle	108 x 103 °
Light distribution	symmetric

Dimensions & weight

Length	1170 mm
Width	83.0 mm
Height	64.0 mm
Product weight	1 kg

Colors & materials

Body material	PC
Product color	grey
Cover material	PC

Temperatures & operating conditions

Additional product data

Product datasheet

Type of cover	cover
Capabilities	
Type of installation	surface-mounted/suspended mounting

Certificates & standards

Protection class	insulation class I (protective earthing)	
Type of protection	IP65	

Country specific categorizations

Order reference	ECOFITZ LED WP

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899467361	ECOFITZ LED WP 1200 40 W C857	Folding carton box 1	1224 mm x 87 mm x 68 mm	7.24 dm ³	1249.00 g
4052899467378	ECOFITZ LED WP 1200 40 W C857	Shipping carton box 9	1242 mm x 276 mm x 214 mm	73.36 dm³	12511.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.