

# **ECOFITZ LED WP 1500 48W C857**

ECOFITZ Water-proof | Damp-proof luminaires







## Product datasheet

#### Technical data

### **Product information**

Order reference	ECOFITZ LED WP
Order reference	ECOFITZ LED WP

#### **Electrical data**

Operating mode	ECG
Nominal wattage	48 W
Connected load	48 W
Nominal voltage	220240 V
Supply voltage	220240 V
Mains frequency	50/60 Hz

## Photometrical data

Color temperature	5700 K
Color temperature [AGMP]	5700 K
Luminous flux	5280 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

# Light technical data

Beam angle	108 x 103 °
Light distribution	symmetric

# **Dimensions & weight**

Length	1450 mm
Width	83.0 mm
Height	64.0 mm
Product weight	1.2 kg

### Colors & materials

Body material	PC
Product color	grey
Cover material	PC

# Temperatures & operating conditions

## Additional product data

# Product datasheet

Type of cover	cover
Canabilities	

# Capabilities

Type of installation	surface-mounted/suspended mounting
----------------------	------------------------------------

### Certificates & standards

Protection class	insulation class I (protective earthing)	
Type of protection	IP65	

# **Country specific categorizations**

Order reference	ECOFITZ LED WP

## Product datasheet

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899467408	ECOFITZ LED WP 1500 48W C857	Folding carton box 1	1504 mm x 87 mm x 68 mm	8.90 dm <sup>3</sup>	1502.00 g
4052899467415	ECOFITZ LED WP 1500 48W C857	Shipping carton box 9	1522 mm x 276 mm x 214 mm	89.90 dm³	15028.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.