





### Technical data

	Product informatio n	Electrical data			
Product description	Order reference	Operating mode	Connected load	Nominal wattage	Nominal voltage
ECOFITZ LED WP 600 20W C840	ECOFITZ LED WP	ECG	20 W	20 W	220240 V
ECOFITZ LED WP 600 20W C857	ECOFITZ LED WP	ECG	20 W	20 W	220240 V
ECOFITZ LED WP 1200 40 W C857	ECOFITZ LED WP	ECG	40 W	40 W	220240 V
ECOFITZ LED WP 1500 48W C857	ECOFITZ LED WP	ECG	48 W	48 W	220240 V

			Photometrical data			
Product description	Supply voltage	Mains frequency	Color temper- ature	Color temperature [AGMP]	Luminous flux	Color render- ing index Ra
ECOFITZ LED WP 600 20W C840	220240 V	50/60 Hz	4000 K	4000 K	2000 lm	>80
ECOFITZ LED WP 600 20W C857	220240 V	50/60 Hz	5700 K	5700 K	2100 lm	>80
ECOFITZ LED WP 1200 40 W C857	220240 V	50/60 Hz	5700 K	5700 K	4400 lm	>80
ECOFITZ LED WP 1500 48W C857	220240 V	50/60 Hz	5700 K	5700 K	5280 lm	>80

		Light technica	ıl data	Dimensions & weight		
Product description	Color rendering index Ra [AGMP]	Beam angle	Light distribution	Length	Width	
ECOFITZ LED WP 600 20W C840	>80	108 x 103 °	symmetric	590.0 mm	83.0 mm	
ECOFITZ LED WP 600 20W C857	>80	108 x 103 °	symmetric	590.0 mm	83.0 mm	
ECOFITZ LED WP 1200 40 W C857	>80	108 x 103 °	symmetric	1170 mm	83.0 mm	
ECOFITZ LED WP 1500 48W C857	>80	108 x 103 °	symmetric	1450 mm	83.0 mm	

		Colors & materials			Temperatures & operating conditions	
Product description	Height	Body material	Product color	Cover material	Ambient temperature range	
ECOFITZ LED WP 600 20W C840	64.0 mm	PC	grey	PC	-20+40 °C	
ECOFITZ LED WP 600 20W C857	64.0 mm	PC	grey	PC	-20+40 °C	
ECOFITZ LED WP 1200 40 W C857	64.0 mm	PC	grey	PC	-20+40 °C	
ECOFITZ LED WP 1500 48W C857	64.0 mm	PC	grey	PC	-20+40 °C	

	Capabilities	Certificates &	& standards
Product description	Type of installation	Protection class	Type of protection
ECOFITZ LED WP 600 20W C840	surface- mounted/suspended mounting	insulation class I (protective earthing)	IP65
ECOFITZ LED WP 600 20W C857	surface- mounted/suspended mounting	insulation class I (protective earthing)	IP65
ECOFITZ LED WP 1200 40 W C857	surface- mounted/suspended mounting	insulation class I (protective earthing)	IP65
ECOFITZ LED WP 1500 48W C857	surface- mounted/suspended mounting	insulation class I (protective earthing)	IP65

### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.