

LEDCOMFO Track Light 15 W 857 24°

LEDCOMFO Track Light 15 W | Indoor LED spotlights



Areas of application

- Retail outlets
- Shops (showcases, displays, sales counters)
- Shopping malls
- Commercial buildings
- Lobbies and corridors
- For indoor use only

Product family benefits

- Deeply recessed cover design to offer good glarecontrol
- Top-level COB platform provides stable quality light
- Combined optics design to offer more even brightness
- Robust housing made of aluminum

Product family features

- Flexible power options: 9W / 15W / 25W / 40W
- Surface and track mounting options
- Dual-circuit track connection compatible with most of the tracks in market
- Rotation angle (horizontal): 355°, swiveling (vertical): 90°
- Beam angle: 15°, 24° and 40°



Product datasheet

Technical data

Product information

| | |
|-----------------|-----------------|
| Order reference | LEDCOMFO TR 15W |
|-----------------|-----------------|

Electrical data

| | |
|-----------------|-------------|
| Operating mode | ECG |
| Nominal wattage | 15 W |
| Connected load | 15 W |
| Nominal voltage | 220...240 V |
| Supply voltage | 220...240 V |
| Mains frequency | 50/60 Hz |

Photometrical data

| | |
|---------------------------------|---------|
| Color temperature | 5700 K |
| Color temperature [AGMP] | 5700 K |
| Luminous flux | 1289 lm |
| Color rendering index Ra | >80 |
| Color rendering index Ra [AGMP] | >80 |

Light technical data

| | |
|--------------------|------------------------|
| Beam angle | 24 ° |
| Light distribution | rotationally symmetric |

Dimensions & weight

| | |
|----------------|----------|
| Length | 127.0 mm |
| Width | 60.0 mm |
| Height | 143.0 mm |
| Product weight | 0.4 kg |

Colors & materials

| | |
|---------------|----------------------------|
| Body material | extruded aluminium section |
| Product color | white |

Temperatures & operating conditions

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

Additional product data

| | |
|---------------|--------|
| Type of cover | lenses |
|---------------|--------|

Product datasheet

Capabilities

| | |
|----------------------|-------------------|
| Type of installation | DIN rail mounting |
|----------------------|-------------------|

Certificates & standards

| | |
|--------------------|---|
| Protection class | insulation class II (safety insulation) |
| Type of protection | IP20 |

Country specific categorizations

| | |
|-----------------|-----------------|
| Order reference | LEDCOMFO TR 15W |
|-----------------|-----------------|

Product datasheet

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-----------------------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4052899481077 | LEDCOMFO Track Light 15 W 857 24° | Folding carton box 1 | 183 mm x 183 mm x 83 mm | 2.78 dm ³ | 518.00 g |
| 4052899481084 | LEDCOMFO Track Light 15 W 857 24° | Shipping carton box 24 | 518 mm x 384 mm x 384 mm | 76.38 dm ³ | 13607.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.