
Product family benefits

- Deeply recessed cover design to offer good glarecontrol
- Top-level COB platform provides stable quality light
- Combined optics design to offer more even brightness
- Robust housing made of aluminum

Product family features

- Beam angle: 15°, 24° and 40°
- Flexible power options: 9W / 15W / 25W / 40W
- Surface and track mounting options
- Dual-circuit track connection compatible with most of the tracks in market
- Rotation angle (horizontal): 355°, swiveling (vertical): 90°



Product family datasheet

Technical data

Product description	Product information	Electrical data			
	Order reference	Operating mode	Nominal wattage	Connected load	Nominal voltage
LEDCOMFO Track Light 40 W 830 15°	LEDCOMFO TR 40W	ECG	40 W	40 W	220...240 V
LEDCOMFO Track Light 40 W 840 15°	LEDCOMFO TR 40W	ECG	40 W	40 W	220...240 V
LEDCOMFO Track Light 40 W 857 15°	LEDCOMFO TR 40W	ECG	40 W	40 W	220...240 V
LEDCOMFO Track Light 40 W 830 24°	LEDCOMFO TR 40W	ECG	40 W	40 W	220...240 V
LEDCOMFO Track Light 40 W 840 24°	LEDCOMFO TR 40W	ECG	40 W	40 W	220...240 V
LEDCOMFO Track Light 40 W 857 24°	LEDCOMFO TR 40W	ECG	40 W	40 W	220...240 V
LEDCOMFO Track Light 40 W 830 40°	LEDCOMFO TR 40W	ECG	40 W	40 W	220...240 V
LEDCOMFO Track Light 40 W 840 40°	LEDCOMFO TR 40W	ECG	40 W	40 W	220...240 V
LEDCOMFO Track Light 40 W 857 40°	LEDCOMFO TR 40W	ECG	40 W	40 W	220...240 V

Product description	Supply voltage	Mains frequency	Photometrical data			
			Color temperature	Color temperature [AGMP]	Luminous flux	Color rendering index Ra
LEDCOMFO Track Light 40 W 830 15°	220...240 V	50/60 Hz	3000 K	3000 K	3012 lm	>80
LEDCOMFO Track Light 40 W 840 15°	220...240 V	50/60 Hz	4000 K	4000 K	3208 lm	>80
LEDCOMFO Track Light 40 W 857 15°	220...240 V	50/60 Hz	5700 K	5700 K	3416 lm	>80
LEDCOMFO Track Light 40 W 830 24°	220...240 V	50/60 Hz	3000 K	3000 K	3012 lm	>80
LEDCOMFO Track Light 40 W 840 24°	220...240 V	50/60 Hz	4000 K	4000 K	3208 lm	>80
LEDCOMFO Track Light 40 W 857 24°	220...240 V	50/60 Hz	5700 K	5700 K	3416 lm	>80
LEDCOMFO Track Light 40 W 830 40°	220...240 V	50/60 Hz	3000 K	3000 K	3012 lm	>80
LEDCOMFO Track Light 40 W 840 40°	220...240 V	50/60 Hz	4000 K	4000 K	3208 lm	>80
LEDCOMFO Track Light 40 W 857 40°	220...240 V	50/60 Hz	5700 K	5700 K	3416 lm	>80

Product description	Color rendering index Ra [AGMP]	Light technical data		Dimensions & weight	
		Beam angle	Light distribution	Length	Width
LEDCOMFO Track Light 40 W 830 15°	>80	15 °	rotationally symmetric	206.0 mm	91.0 mm
LEDCOMFO Track Light 40 W 840 15°	>80	15 °	rotationally symmetric	206.0 mm	91.0 mm
LEDCOMFO Track Light 40 W 857 15°	>80	15 °	rotationally symmetric	206.0 mm	91.0 mm

Product family datasheet

Product description	Color rendering index Ra [AGMP]	Light technical data		Dimensions & weight	
		Beam angle	Light distribution	Length	Width
LEDCOMFO Track Light 40 W 830 24°	>80	24 °	rotationally symmetric	206.0 mm	91.0 mm
LEDCOMFO Track Light 40 W 840 24°	>80	24 °	rotationally symmetric	206.0 mm	91.0 mm
LEDCOMFO Track Light 40 W 857 24°	>80	24 °	rotationally symmetric	206.0 mm	91.0 mm
LEDCOMFO Track Light 40 W 830 40°	>80	40 °	rotationally symmetric	206.0 mm	91.0 mm
LEDCOMFO Track Light 40 W 840 40°	>80	40 °	rotationally symmetric	206.0 mm	91.0 mm
LEDCOMFO Track Light 40 W 857 40°	>80	40 °	rotationally symmetric	206.0 mm	91.0 mm

Product description	Height	Colors & materials		Temperatures & operating conditions	Capabilities
		Body material	Product color	Ambient temperature range	Type of installation
LEDCOMFO Track Light 40 W 830 15°	175.0 mm	extruded aluminium section	white	-20...+40 °C	DIN rail mounting
LEDCOMFO Track Light 40 W 840 15°	175.0 mm	extruded aluminium section	white	-20...+40 °C	DIN rail mounting
LEDCOMFO Track Light 40 W 857 15°	175.0 mm	extruded aluminium section	white	-20...+40 °C	DIN rail mounting
LEDCOMFO Track Light 40 W 830 24°	175.0 mm	extruded aluminium section	white	-20...+40 °C	DIN rail mounting
LEDCOMFO Track Light 40 W 840 24°	175.0 mm	extruded aluminium section	white	-20...+40 °C	DIN rail mounting
LEDCOMFO Track Light 40 W 857 24°	175.0 mm	extruded aluminium section	white	-20...+40 °C	DIN rail mounting
LEDCOMFO Track Light 40 W 830 40°	175.0 mm	extruded aluminium section	white	-20...+40 °C	DIN rail mounting
LEDCOMFO Track Light 40 W 840 40°	175.0 mm	extruded aluminium section	white	-20...+40 °C	DIN rail mounting
LEDCOMFO Track Light 40 W 857 40°	175.0 mm	extruded aluminium section	white	-20...+40 °C	DIN rail mounting

Product description	Certificates & standards	
	Protection class	Type of protection
LEDCOMFO Track Light 40 W 830 15°	insulation class II (safety insulation)	IP20
LEDCOMFO Track Light 40 W 840 15°	insulation class II (safety insulation)	IP20

Product family datasheet

Product description	Certificates & standards	
	Protection class	Type of protection
LEDCOMFO Track Light 40 W 857 15°	insulation class II (safety insulation)	IP20
LEDCOMFO Track Light 40 W 830 24°	insulation class II (safety insulation)	IP20
LEDCOMFO Track Light 40 W 840 24°	insulation class II (safety insulation)	IP20
LEDCOMFO Track Light 40 W 857 24°	insulation class II (safety insulation)	IP20
LEDCOMFO Track Light 40 W 830 40°	insulation class II (safety insulation)	IP20
LEDCOMFO Track Light 40 W 840 40°	insulation class II (safety insulation)	IP20
LEDCOMFO Track Light 40 W 857 40°	insulation class II (safety insulation)	IP20

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.