

LEDCOMFO SL HP 6 W 830 24°

LEDCOMFO Spot Light HP 6 W | Indoor LED spotlights



Areas of application

- For indoor use only
- Display case lighting
- Commercial buildings
- Retail outlets
- Shopping malls
- Lobbies and corridors

Product family benefits

- Concave stepping cover design
- Reflector to reduce glare and light pollution
- High light uniformity
- Top-level COB platform provides stable quality light
- Die-casting housing
- Spray finished metal rim provides rich product textures

Product family features

- Beam angle: 15°, 24° and 40°
- 30° vertical adjustable
- Flexible power options: 6W / 9W / 18W / 30W



non EU



Product datasheet

Technical data

Product information

Order reference	LEDCOMFO SL HP
-----------------	----------------

Electrical data

Operating mode	ECG
Nominal wattage	6 W
Connected load	6 W
Nominal voltage	220...240 V
Supply voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Color temperature [AGMP]	3000 K
Luminous flux	472 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

Light technical data

Beam angle	24 °
Light distribution	symmetric

Dimensions & weight

Length	0.0 mm
Diameter	77.0 mm
Height	59.0 mm
Product weight	0.2 kg

Colors & materials

Body material	diecast aluminium
Product color	black
Cover material	PC

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Product datasheet

Type of cover	cover
---------------	-------

Capabilities

Type of installation	recessed
----------------------	----------

Certificates & standards

Protection class	insulation class II (safety insulation)
Type of protection	IP20

Country specific categorizations

Order reference	LEDCOMFO SL HP
-----------------	----------------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899479289	LEDCOMFO SL HP 6 W 830 24°	Folding carton box 1	115 mm x 105 mm x 85 mm	1.03 dm ³	243.00 g
4052899479296	LEDCOMFO SL HP 6 W 830 24°	Shipping carton box 48	485 mm x 335 mm x 365 mm	59.30 dm ³	12642.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.