

LEDCOMFO SL HP 18 W 830 24°

LEDCOMFO Spot Light HP 18 W | Indoor LED spotlights



Areas of application

- Display case lighting
- Commercial buildings
- Retail outlets
- Shopping malls
- Lobbies and corridors
- For indoor use only

Product family benefits

- Concave stepping cover design
- Reflector to reduce glare and light pollution
- High light uniformity
- Top-level COB platform provides stable quality light
- Die-casting housing
- Spray finished metal rim provides rich product textures

Product family features

– Beam angle: 15° , 24° and 40°

- 30° vertical adjustable

– Flexible power options: 6W / 9W / 18W / 30W





Product datasheet

Technical data

Product information

Order reference	LEDCOMFO SL HP
-----------------	----------------

Electrical data

Operating mode	ECG
Nominal wattage	18 W
Connected load	18 W
Nominal voltage	220240 V
Supply voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Color temperature [AGMP]	3000 K
Luminous flux	1309 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

Light technical data

Beam angle	24 °
Light distribution	symmetric

Dimensions & weight

Length	0.0 mm
Diameter	111.0 mm
Height	85.0 mm
Product weight	0.4 kg

Colors & materials

Body material	diecast aluminium
Product color	black
Cover material	PC

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Additional product data

Product datasheet

Capabilities

Type of installation	recessed
----------------------	----------

Certificates & standards

Protection class	insulation class II (safety insulation)	
Type of protection	IP20	

Country specific categorizations

Order reference	LEDCOMFO SL HP

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899479647	LEDCOMFO SL HP 18 W 830 24°	Folding carton box 1	140 mm x 125 mm x 125 mm	2.19 dm³	565.00 g
4052899479654	LEDCOMFO SL HP 18 W 830 24°	Shipping carton box 36	512 mm x 432 mm x 390 mm	86.26 dm ³	21652.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.