

# LEDCOMFO SL HP 30 W 840 40°

LEDCOMFO Spot Light HP 30 W | Indoor LED spotlights



#### Areas of application

- Display case lighting
- Commercial buildings
- Retail outlets
- Shopping malls
- Lobbies and corridors
- For indoor use only

### Product family benefits

- Concave stepping cover design
- Reflector to reduce glare and light pollution
- High light uniformity
- Top-level COB platform provides stable quality light
- Die-casting housing
- Spray finished metal rim provides rich product textures

#### Product family features

– Beam angle:  $15^{\circ}$ ,  $24^{\circ}$  and  $40^{\circ}$ 

- 30° vertical adjustable

– Flexible power options: 6W / 9W / 18W / 30W





# Product datasheet

#### Technical data

#### **Product information**

Order reference	LEDCOMFO SL HP
-----------------	----------------

#### **Electrical data**

Operating mode	ECG
Nominal wattage	30 W
Connected load	30 W
Nominal voltage	220240 V
Supply voltage	220240 V
Mains frequency	50/60 Hz

### Photometrical data

Color temperature	4000 К
Color temperature [AGMP]	4000 K
Luminous flux	2480 lm
Color rendering index Ra	>80
Color rendering index Ra [AGMP]	>80

### Light technical data

Beam angle	40 °
Light distribution	symmetric

# Dimensions & weight

Length	0.0 mm
Diameter	140.0 mm
Height	106.0 mm
Product weight	0.7 kg

#### Colors & materials

Body material	diecast aluminium	
Product color	black	
Cover material	PC	

## Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

### Additional product data

# Product datasheet

Type of cover cover
---------------------

# Capabilities

Type of installation	recessed
----------------------	----------

### Certificates & standards

Protection class	insulation class II (safety insulation)	
Type of protection	IP20	

# **Country specific categorizations**

Order reference	LEDCOMFO SL HP
-----------------	----------------

### Product datasheet

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899479906	LEDCOMFO SL HP 30 W 840 40°	Folding carton box 1	152 mm x 142 mm x 131 mm	2.83 dm <sup>3</sup>	868.00 g
4052899479913	LEDCOMFO SL HP 30 W 840 40°	Shipping carton box 24	580 mm x 477 mm x 277 mm	76.63 dm³	22172.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.