

OPTIVALU PANEL G2 600x600

Indoor LED ceiling luminaires



Areas of application

- Hospitals
- Offices
- Banks
- Floodlight for high buildings
- Streets, city squares, stations

Product family benefits

- Slim and compact design (10 mm thickness)
- High luminance uniformity
- Good color consistency
- Even color, no dark or hot spot
- Energy savings of up to 30 % compared to T5/T8 louver)

Product family features

- Long lifetime: up to 50,000 h
- For recessed, suspended and ceiling mounting



non EU



Product family datasheet

Technical data

Product description	Product information	Electrical data			
	Order reference	Operating mode	Connected load	Nominal wattage	Supply voltage
OPTIVALU Panel G2 LP 0606 840 DA	OPTV PANEL G2 L	ECG	26 W	26 W	220...240 V
OPTIVALU Panel G2 LP 0606 840	OPTV PANEL G2 L	ECG	26 W	26 W	220...240 V
OPTIVALU Panel G2 LP 0606 865	OPTV PANEL G2 L	ECG	26 W	26 W	220...240 V

Product description	Nominal voltage	Mains frequency	Photometrical data			
			Color temperature [AGMP]	Color temperature	Luminous flux	Color rendering index Ra [AGMP]
OPTIVALU Panel G2 LP 0606 840 DA	220...240 V	50/60 Hz	4000 K	4000 K	2860 lm	>80
OPTIVALU Panel G2 LP 0606 840	220...240 V	50/60 Hz	4000 K	4000 K	2860 lm	>80
OPTIVALU Panel G2 LP 0606 865	220...240 V	50/60 Hz	6500 K	6500 K	2860 lm	>80

Product description	Color rendering index Ra	Light technical data	Dimensions & weight			Colors & materials
		Beam angle	Length	Width	Height	Body material
OPTIVALU Panel G2 LP 0606 840 DA	>80	115 °	597.0 mm	597.0 mm	10.0 mm	steel
OPTIVALU Panel G2 LP 0606 840	>80	115 °	597.0 mm	597.0 mm	10.0 mm	steel
OPTIVALU Panel G2 LP 0606 865	>80	115 °	597.0 mm	597.0 mm	10.0 mm	steel

Product description	Product color	Cover material	Temperatures & operating conditions	Capabilities
			Ambient temperature range	Type of installation
OPTIVALU Panel G2 LP 0606 840 DA	white	PMMA	-20...+35 °C	lay-in mounting/suspended mounting
OPTIVALU Panel G2 LP 0606 840	white	PMMA	-20...+35 °C	lay-in mounting/suspended mounting
OPTIVALU Panel G2 LP 0606 865	white	PMMA	-20...+35 °C	lay-in mounting/suspended mounting

Product family datasheet

Product description	Certificates & standards	
	Protection class	Type of protection
OPTIVALU Panel G2 LP 0606 840 DA	insulation class II (safety insulation)	IP20
OPTIVALU Panel G2 LP 0606 840	insulation class II (safety insulation)	IP20
OPTIVALU Panel G2 LP 0606 865	insulation class II (safety insulation)	IP20

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.