

LEDCOMFO Multi-head 2X9 W 857 40°

LEDCOMFO Multi-head 2X9W | Indoor LED spotlights



Areas of application

- Display lighting
- Commercial buildings
- Retail outlets
- Shopping malls
- Lobbies and corridors
- Households
- For indoor use only

Product family benefits

- Die-casting housing
- Easy fit in different architectural structures
- More than 50 % energy savings compared to traditional multi-head spot light
- Good glare control thanks to concave stepping cover design

Product family features

- Beam angle: 15°, 24° and 40°
- 30° vertical adjustable, 180° horizontal adjustable
- Flexible product options: 2 head arrangements
- Individual driver for each module
- Failure of single module won't affect others
- Easy installation thanks to rimless design



non EU



Product datasheet

Technical data

Product information

| | |
|-----------------|-----------------|
| Order reference | LDCMF MULTI-HEA |
|-----------------|-----------------|

Electrical data

| | |
|-----------------|-------------|
| Operating mode | ECG |
| Nominal wattage | 18 W |
| Connected load | 18 W |
| Lamp wattage | 9 W |
| Nominal voltage | 220...240 V |
| Supply voltage | 220...240 V |
| Mains frequency | 50/60 Hz |

Photometrical data

| | |
|---------------------------------|---------|
| Color temperature | 5700 K |
| Color temperature [AGMP] | 5700 K |
| Luminous flux | 1443 lm |
| Color rendering index Ra | >80 |
| Color rendering index Ra [AGMP] | >80 |

Light technical data

| | |
|--------------------|-----------|
| Beam angle | 40 ° |
| Light distribution | symmetric |

Dimensions & weight

| | |
|----------------|----------|
| Length | 216.0 mm |
| Width | 113.0 mm |
| Height | 82.0 mm |
| Product weight | 0.8 kg |

Colors & materials

| | |
|----------------|-----------|
| Body material | aluminium |
| Product color | black |
| Cover material | PC |

Temperatures & operating conditions

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

Product datasheet

Additional product data

| | |
|----------------------------|-------|
| Number of lighting outlets | 2 |
| Type of cover | cover |

Capabilities

| | |
|----------------------|----------|
| Type of installation | recessed |
|----------------------|----------|

Certificates & standards

| | |
|--------------------|---|
| Protection class | insulation class II (safety insulation) |
| Type of protection | IP20 |

Country specific categorizations

| | |
|-----------------|-----------------|
| Order reference | LDCMF MULTI-HEA |
|-----------------|-----------------|

Product datasheet

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-----------------------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4052899483392 | LEDCOMFO Multi-head 2X9 W 857 40° | Folding carton box 1 | 277 mm x 145 mm x 110 mm | 4.42 dm ³ | 965.00 g |
| 4052899483408 | LEDCOMFO Multi-head 2X9 W 857 40° | Shipping carton box 12 | 575 mm x 455 mm x 235 mm | 61.48 dm ³ | 12725.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.