

SUNNY T5 HI-BAY II 4X Grid Cover

SUNNY T5 Hi-bay II 4X | High-bay luminaires



Areas of application

- Logistics halls
- High ceiling (e.g. in shopping malls, airports, commercial buildings, lobbies)
- Factories
- For indoor use only

Product family benefits

- Compact and robust design

Product family features

- High-quality aluminum reflector
- High reliability
- Complete portfolio with 2X54 W to 6X54 W



Product datasheet

Technical data

Product information

Order reference	SUNNY T5 HI-BAY
-----------------	-----------------

Electrical data

Operating mode	ECG
Nominal voltage	220...240 V
Supply voltage	220...240 V
Mains frequency	50/60 Hz

Light technical data

Beam angle	wide distribution °
------------	---------------------

Dimensions & weight

Length	1180 mm
Width	254.0 mm
Height	87.0 mm
Product weight	3 kg

Colors & materials

Body material	steel
Product color	white

Temperatures & operating conditions

Ambient temperature range	-15...+40 °C
---------------------------	--------------

Additional product data

Number of lighting outlets	4
----------------------------	---

Capabilities

Type of installation	suspended mounting
----------------------	--------------------

Certificates & standards

Protection class	insulation class I (protective earthing)
Type of protection	IP20

Country specific categorizations

Order reference	SUNNY T5 HI-BAY
-----------------	-----------------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899470675	SUNNY T5 HI-BAY II 4X Grid Cover	Shipping carton box 2	1245 mm x 250 mm x 320 mm	99.60 dm ³	7480.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.