Product family datasheet

LEDriving SL P27/7W YELLOW

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Amber



Replaces conventional P277W lamps Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P27/7W

LEDriving SL P27/7W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P27/7W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Product in | formation | | General Product Information | Electrical D | ata |
|-------------------------------------------|------------------------------------------|-----------------------------|-----------------------------------------------|-----------------------------------------------------------|-----------------------------------------|----------------------------------|
| Product description | Application and Produc | n (Category ct specific) | Product type (off- road vs. on-road) | Global order reference | Power input | Nominal voltage |
| LEDriving SL \triangleq P27/7W | Mainly use signal/ ind applicatior | icator | Off-road ≙ P27/7W | 3157DYP | 1.7 W | 12.0 V |
| | | | | Photometric Data | | Physical Attributes & Dimensions |
| Product description | Nominal w | attage | Test voltage | flux | Luminous flux | Diameter |
| | | | | | tolerance | |
| LEDriving SL ≜ P27/7W | 1 W | | 13.5 V | | tolerance ±25 % | 25.7 mm |
| LEDriving SL ≜ P27/7W | 1 W | ata | 13.5 V Capabilities | | ±25 % Latory Inform Art. 33 of EU | ation |
| LEDriving SL ≜ P27/7W Product description | | ata Lifespan Tc | | 55/10 lm Environmental & Regu Information according | ±25 % Latory Inform Art. 33 of EU | ation |

| Product description | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|-----------------------|---------------------------|-------------------------------------------------------------------------------------------------------------------|------------------------------------------|
| LEDriving SL ≙ P27/7W | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | ac938de6-4f2b-4a13- b03a-b2c2a077f305 |

 $^{1)}$ Light-emitting diode lamp

Product family datasheet

Download Data

 File

 Image: Second s

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.