

LEDDriving SL W5W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional W5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for W5W

LEDDriving SL W5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional W5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description | Product information | | | Electrical data | | |
|-----------------------------|---------------------|-------------------------------------|--|-----------------|-----------------|-----------------|
| | Order reference | Product type (off-road vs. on-road) | Application (Category and Product specific) | Power input | Nominal voltage | Nominal wattage |
| LEDDriving SL $\hat{=}$ W5W | 2825DWP | Off-road $\hat{=}$ W5W | Mainly used for signal/ indicator/ interior applications | 1.12 W | 12.0 V | 0.80 W |

| Product description | Test voltage | Photometrical data | | Dimensions & weight | Lifespan | | Capabilities |
|-----------------------------|--------------|--------------------|-------------------------|---------------------|-------------|-------------|-------------------|
| | | Luminous flux | Luminous flux tolerance | Diameter | Lifespan B3 | Lifespan Tc | Technology |
| LEDDriving SL $\hat{=}$ W5W | 13.5 V | 70 lm | \pm 25 % | 10.0 mm | 1500 h | 4000 h | LED ¹⁾ |

| Product description | Environmental information | | | |
|-----------------------------|---|---|----------------------------|------------------------|
| | Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | | | |
| Product description | Date of Declaration | Primary Article Identifier | Candidate List Substance 1 | CAS No. of substance 1 |
| LEDDriving SL $\hat{=}$ W5W | 19-04-2024 | 4052899620810 4062172348638 4062172352055 4062172401258 4062172408295 | Lead | 7439-92-1 |

| Product description | Safe Use Instruction | Declaration No. in SCIP database |
|-----------------------------|--|--------------------------------------|
| LEDDriving SL $\hat{=}$ W5W | The identification of the Candidate List substance is sufficient to allow safe use of the article. | d493a7ba-1e50-4adf-97d4-fe52b1e7a9c4 |

¹⁾ Light-emitting diode lamp

Product family datasheet

Download Data

| File | |
|---|---|
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.