## Product datasheet

# BATTERYcharge 7PIN | 3PHASE | 32 AMP

Charging Cable for electric and plug-in hybrid vehicles



Type 2 to Type 2 Charge at home and on the moveType 2 to Type 27PIN | 3PHASE



**32 Ampere** Connects to any charging unit or station with a 32A (3 Phase) type 2 connection



22 kWh Charge your 60kW battery in ca. 3 hours



OSRAM

5m cable length Ergonomic handles for optimal handling and a cable length of 5 meters

#### Drive with OSRAM into a more emission-free future



Discover the world of electric driving with OSRAM. Charge your all-electric or plug-in hybrid vehicle from type 2 at any compatible charging station equipped with a 32A (3-phase) type 2 connection. The charging cable is equipped with ergonomic handles for optimal handling and has a cable length of 5 meters. It is suitable for use at public charging stations and at home. In addition, the charging cables are equipped with dust protection caps and tested for water resistance according to IP65 and shock resistance according to IK10. Even when connected, the electrical contact points are protected against the ingress of dust and splash water in accordance with IP65 and IK10. The scope of delivery also includes a durable, compact storage bag to neatly store the cable after charging. In addition, the product is TÜV and CE certified and comes with a 2-year guarantee\*

# Product datasheet

#### Technical data

## **Product information**

| Storage Case                | Yes   |
|-----------------------------|-------|
| Number Of Phases            | 3     |
| Vehicle Charger Type        | Туре2 |
| Charging Point Charger Type | Туре2 |

## **General Product Information**

|--|

#### **Electrical Data**

| Nominal wattage | 22000 W |
|-----------------|---------|
| Nominal voltage | 480 V   |
| Nominal current | 32 A    |

#### **Physical Attributes & Dimensions**

| Length | 5000 mm  |
|--------|----------|
| Width  | 70.0 mm  |
| Height | 120.0 mm |

## Lifetime Data

| Guarantee 2 years |
|-------------------|
|-------------------|

#### Additional product data

| Operating Temperature -40 +80 °C |
|----------------------------------|
|----------------------------------|

#### **Certificates & standards**

| Type of protection | IP65     |
|--------------------|----------|
| Standards          | TÜV / CE |
| IK Class           | IK10     |

#### **Environmental & Regulatory Information**

## Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

| Date of declaration              | 26-06-2024                         |  |
|----------------------------------|------------------------------------|--|
| Primary article identifier       | 4052899624139                      |  |
| Candidate list substance 1       | No declarable substances contained |  |
| Declaration no. in SCIP database | In work                            |  |

# Product datasheet

#### Logistical Data

| Product code  | Product description                         | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume                | Gross weight |
|---------------|---|---------------------------------|---|-----------------------|--------------|
| 4052899624207 | BATTERY charge<br>7PIN   3PHASE   32<br>AMP |                                 | - x - x -                               | 77.93 dm <sup>3</sup> |              |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Legal advice

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.\*for precise conditions please refer to:

www.osram.com/am-guarantee

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

