

LEDDriving SL T5

Ideal replacement for any vehicle



Suitable for various vehicle interior and exterior applications

Available in Cool White



Replaces conventional T5 lamps (e.g. ECE W2.3W)

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for T5 (e.g. W2.3W)

LEDDriving SL T5 replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional T5 lamp bases (e.g. ECE W2.3W). In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description | Product information | | General Product Information | Electrical Data | |
|--------------------------------------|-------------------------------------|--|-----------------------------|-----------------|-----------------|
| | Product type (off-road vs. on-road) | Application (Category and Product specific) | Global order reference | Power input | Nominal voltage |
| LEDriving SL \triangleq W2.3W (T5) | Off-road \triangleq W2.3W (T5) | Mainly used for signal/ indicator applications | 2723DWP | 0.25 W | 12.0 V |

| Product description | Nominal wattage | Power input tolerance | Test voltage | Photometric Data | Physical Attributes & Dimensions |
|--------------------------------------|-----------------|-----------------------|--------------|-----------------------|----------------------------------|
| | | | | Nominal luminous flux | Lamp base |
| LEDriving SL \triangleq W2.3W (T5) | 0 W | ± 20 % | 13.5 V | 25 lm | W2x4.6d |

| Product description | Length | Diameter | Lifetime Data | | Capabilities |
|--------------------------------------|---------|----------|---------------|-------------|-------------------|
| | | | Lifespan B3 | Lifespan Tc | Technology |
| LEDriving SL \triangleq W2.3W (T5) | 16.5 mm | 6 mm | 750 hr | 2000 hr | LED ¹⁾ |

| Product description | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | | |
|--------------------------------------|---|-------------------------------|----------------------------------|
| | Date of declaration | Primary article identifier | Declaration no. in SCIP database |
| LEDriving SL \triangleq W2.3W (T5) | 09-07-2024 | 4062172254687 4062172401838 | In work |

¹⁾ Light-emitting diode lamp

Product family datasheet

Download Data

| File | |
|---|---|
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.