

# TYREinflate Connect 650



### Download via App

The smart app stores the tyre pressure for your car and downloads it to the OSRAM TYREinflate Connect 650



### Auto Stop function

Auto Stop function when pre-set pressure is reached.



### Leak Detection

Including function to detect a loss of tyre pressure



### OSRAMconnect

Connecting you with your car



### OSRAMconnect App compatible tyre inflator

Improve your driving performance and fuel costs by making sure your tyre pressure is correct. The OSRAM TYREinflate Connect 650 is a digital tyre inflator compatible with the OSRAMconnect app, with a backlit display for easy and accurate pressure measurement and inflation<sup>3)</sup> of tyres, showing pressure values in BAR, kPA and PSI. The app can store up to 5 vehicles and the associated information and has a function to detect a loss of tyre pressure. Furthermore, the OSRAM TYREinflate Connect 650 has an automatic switch-off function as soon as the preset pressure is reached. In addition, it has a storage compartment for valve caps, a 3.3 m long retractable power cable with a 12V fuse plug, a 65 cm long flexible air hose with an easily accessible holder and an additional LED light for illumination at night or in poor lighting conditions and a large on/off switch for additional manual operation. An inflation time of about 3 minutes<sup>2)</sup> gets you on the road and where you need to be fast. Also included is a 3-piece adapter set, for bikes, balls and other inflatables, and a durable storage bag. OSRAM provides a 2-year guarantee on this product<sup>1)</sup>1) For precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)2) Based on inflating a 13" tyre from flat to 2.41 BAR3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

## Product family datasheet

### Technical data


Product description	General Product Information	Electrical Data	Physical Attributes & Dimensions	
	Global order reference	Nominal voltage	Length	Width
TYRE inflate Connect 650	OTIC650	11.1 V	200.0 mm	90.0 mm

Product description	Height	Operating Conditions	Additional product data	Capabilities
		Noise Level (dB)	Display Type	Fuse
TYRE inflate Connect 650	219.0 mm	90 dB	Digital	10 A

Product description	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Date of declaration	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
TYRE inflate Connect 650	05-09-2024	4052899622883	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
TYRE inflate Connect 650	The identification of the Candidate List substance is sufficient to allow safe use of the article.	f2f01f10-b494-4e57-ad3c-e7f344875985

### Download Data

File	
	User instruction TYREinflate Connect 650

#### Safety advice

Reaches a maximum noise level of 90 db.

#### Legal advice

1) For precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

2) Based on inflating a 13" tyre from flat to 2.41 BAR

3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres  
Application advice: For more detailed application information and graphics please see product datasheet and the user instruction.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.