

TYREinflate 6000

TYREinflate 6000 OTIR 6000



Rapid Inflation Time

Inflate the tyre to the desired pressure in approximately 2 minutes 1)2)



Deflator Valve

For deflating too much air



Digital Auto Stop

Automatic stop function when the preset pressure is reached



Cordless and rechargeable

Can be used with or without direct power supply

Product family datasheet



Rechargeable Digital Tyre Inflator and Air Pump

The OSRAM TYREinflate 6000 is a cordless and rechargeable tyre inflator with Li-Ion battery, making it an ideal companion for camping and road trips. The OTIR 6000 digital tyre inflator can inflate a tyre in just two minutes¹⁾²⁾ and has a special setting for other inflatable items such as air beds, air mattresses, balls and more. The auto stop function and the deflator valve help to keep the tyres and other inflatables optimally inflated. . The backlit LED display and integrated LED light provide improved readability of the pressure settings and improved illumination of the working area even in reduced visibility conditions or at night. Thanks to the powerbank function, the OSRAM TYREinflate 6000 can also be used as a charger for electronic devices such as your mobile phone. The scope of delivery includes a mains charger and a 12-volt cable for direct power supply, if required. Also included is a 10-piece adapter set, a storage bag and spare valve caps. OSRAM offers a 2-year guarantee¹⁾ on this product.

1) For precise conditions please refer to: www.osram.com/am-guarantee²⁾ Based on inflating a 13" tyre from flat to 2.4 BAR
3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Product family datasheet

Technical data

| Product description | Product information | | | |
|---------------------|---------------------|-----------|-----------------|-----------|
| | Deflation valve | LED Light | Preset Function | Auto stop |
| TYRE inflate 6000 | Yes | Yes | Yes | Yes |


| Product description | Storage Case | General Product Information | Electrical Data | Physical Attributes & Dimensions |
|---------------------|--------------|-----------------------------|-----------------|----------------------------------|
| | | Global order reference | Nominal voltage | Length |
| TYRE inflate 6000 | Yes | OTIR6000 | 12.0 V | 298.0 mm |

| Product description | Width | Height | Operating Conditions | Additional product data |
|---------------------|----------|---------|----------------------|-------------------------|
| | | | Noise Level (dB) | Display Type |
| TYRE inflate 6000 | 298.0 mm | 80.0 mm | 90 dB | Digital |

| Product description | USB Socket 2.1A (For other Devices) | Extras | Capabilities | Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |
|---------------------|-------------------------------------|--------------------------------------------------------------------------------|--------------|--------------------------------------------------------------------------------------------------|
| | | | Fuse | Date of declaration |
| TYRE inflate 6000 | Yes | 10-piece adaptor kit & 4 x spare valve caps, 1 x spare fuse & 1 pair of gloves | 15 A | 26-06-2024 |

| Product description | Candidate list substance 1 | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|---------------------|----------------------------|------------------------|----------------------------------------------------------------------------------------------------|--------------------------------------|
| TYRE inflate 6000 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 3abae9a3-29bd-403e-915c-caab5002583a |

Download Data

| File | |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
|  | User instruction TYREinflate OTIR6000 Rechargeable Digital Tyre Inflator and Air Pump |

Legal advice

- 1) For precise conditions please refer to: www.osram.com/am-guarantee
 - 2) Based on inflating a 13" tyre from flat to 2.41 BAR
 - 3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres
- Application advice: For more detailed application information and graphics please see product datasheet and the user instruction.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.