Product family datasheet

LEDriving HL BRIGHT H1

Up to +300% more brightness

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner. Compared to minimum ECE R112, for H7/H18 & H4/H19

Very compact LED replacement for conventional H1 high and low beam lamps

Reduced glaring thanks to an optimized light distribution

Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect

4 year OSRAM guarantee

For precise conditions, please refer to www.osram.com/am-guarantee

High-performing LED retrofit lamp providing improved visibility and a stylish look

With up to +300% more brightness (compared to ECE R112, for H7/H18 & H4/H19), the OSRAM LEDriving HL BRIGHT retrofit lamp ensures optimum visibility and thus allowing drivers to recognize signs, obstacles and hazards sooner than conventional lamps. This LED retrofit lamp not only creates a stylish modern look with a cool white color temperature of 6,000K but also offers reduced glaring thanks to an optimized light distribution. Premium OSRAM quality and LED technology grant up to 5 times more lifetime (compared to ECE R112) and better visibility thanks to daylight effect. The pair of lamps comes with a 4-year OSRAM guarantee. For precise guarantee conditions please refer to www.osram.com/am-guarantee.The LEDriving HL BRIGHT high and low beam lamps by OSRAM replace conventional halogen lamps and are 12V compatible. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

© 2024, OSRAM GmbH. All rights reserved.

Product family datasheet

Technical data

	Product information		General Product Information	Electrical Data	
Product description	**Product type (off-road vs. on-road)**	**Application (Category and Product specific)**	**Global order reference**	**Power input**	**Nominal voltage**
LEDriving HL BRIGHT ≙ H1	Off-road ≙ H1	Mainly used for Low Beam, High Beam and Fog light applications	64150DWBRT	13 W	12.0 V

		Photometric Data		Physical Attributes & Dimensions	Lifetime Data
Product description	**Nominal wattage**	**Nominal luminous flux**	**Luminous flux tolerance**	**Diameter**	**Lifespan Tc**
LEDriving HL BRIGHT ≙ H1	13 W	1500 lm	±20 %	14.0 mm	5000 hr

	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	**Technology**	**Date of declaration**	**Primary article identifier**	**Declaration no. in SCIP database**
LEDriving HL BRIGHT ≙ H1	LED	26-06-2024	4062172315579	In work

© 2024, OSRAM GmbH. All rights reserved.

Product family datasheet

Download Data

	File
	User instruction LEDriving HL BRIGHT
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, OSRAM GmbH. All rights reserved.