


# LCD Remote Screen



**Compatible with both 12V and 24V Modified and Pure Sine Wave POWERinvert PRO inverters**

Works with all OSRAM POWERinvert PRO inverters




**Multifunction Readings**  
1. DC Voltage Input  
2. AC Voltage Output  
3. Continuous Wattage  
4. Amp hour

Full picture of how the inverter is performing and the state of health the vehicle's battery



**6m of Cable**

So it can be mounted in an accessible area away from the inverter



**Complemented by the LCD frame (OINVFRM) for secure housing**

Bracket provides additional protection to the screen and secure fixing



### Accessories for inverter

OSRAM POWERinvert PRO is an extensive range of professional heavy duty inverters for remote working. Available in either Pure Sine Wave or Modified Sine Wave for both 12V and 24V applications. OSRAM POWERinvert Pro inverters take the 12V or 24V DC vehicle electrical supply and invert into 230V AC mains power to run and operate electrical equipment from service vehicles. Pure Sine Wave Inverters produce a sine wave with the same frequency as mains power, with no distortion, to power sensitive electronics. Modified Inverters have distorted frequency, meaning they will power less complicated products such as fridges and power tools.

## Product family datasheet

### Technical data

| Product description       | Product information                         | Physical Attributes & Dimensions |         |         |
|---------------------------|---|----------------------------------|---------|---------|
|                           | Application (Category and Product specific) | Length                           | Width   | Height  |
| LCD Remote Screen OINVLCD | Inverter accessory                          | 70.0 mm                          | 27.8 mm | 99.5 mm |

| Product description       | Dimensions & weight        | Certificates & standards          | Environmental & Regulatory Information<br>Information according Art. 33 of EU<br>Regulation (EC) 1907/2006 (REACH) |                            |
|---------------------------|----------------------------|-----------------------------------|--|----------------------------|
|                           | Input Cable Gauge / Length | Standards                         | Date of declaration  | Primary article identifier |
| LCD Remote Screen OINVLCD | 6 m                        | CE-EMC / ROHS /<br>WEEE / E- Mark | 19-08-2024   | 4052899631113              |

| Product description       | Candidate list<br>substance 1 | CAS No. of substance<br>1 | Safe use instruction  | Declaration no. in<br>SCIP database          |
|---------------------------|-------------------------------|---------------------------|---|--|
| LCD Remote Screen OINVLCD | Lead                          | 7439-92-1                 | The identification of<br>the Candidate List<br>substance is<br>sufficient to allow<br>safe use of the<br>article. | 363f17b5-80dd-<br>4aa6-8573-<br>ec6b4071bd21 |

## Product family datasheet

### **Safety advice**

Tested and certified to the relevant EMC and LVD Directives.

### **Legal advice**

CE ApprovedRoHS and WEEE Approved.

### **Application advice**

For more detailed application information and graphics please see product datasheet.

### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.